

# Firestone

ULTRA HIGH PERFORMANCE		LIGHT TRUCK / SUV ALL-TERRAIN	
Firehawk INDY 500®.....	200	Destination A/T2.....	222
Firehawk ASV2.....	202	Destination X/T.....	224
TOURING		LIGHT TRUCK / SUV MAX-TRACTION	
WeatherGrip.....	204	Destination M/T2.....	226
FR710.....	206	LIGHT TRUCK / COMMERCIAL HIGHWAY	
FR140.....	208	Transforce HT2.....	228
PASSENGER		Transforce CV.....	230
All Season.....	210	LIGHT TRUCK / COMMERCIAL ALL-TERRAIN	
Firehawk GTV.....	212	Transforce AT2.....	232
LAW ENFORCEMENT / HIGH-SPEED EMERGENCY		WINTER	
Firehawk Pursuit.....	214	WinterForce 2.....	234
Firehawk Pursuit AWT.....	216	WinterForce 2 UV.....	236
LIGHT TRUCK / SUV HIGHWAY		WinterForce LT.....	238
Destination LE3.....	218	WinterForce CV.....	240
Destination LE2.....	220		

TIRE SPECIFICATIONS CURRENT AT TIME OF PUBLICATION

## TIRE RESOURCE MANUAL

# FIREHAWK™ INDY 500®

ULTRA-HIGH SUMMER PERFORMANCE



## ULTRA-HIGH SUMMER PERFORMANCE AT A GREAT VALUE

### Features & Benefits




Summer performance



Confident water evacuation for more control on wet roads



Ultra-high performance with bold design



#### Proprietary Pulse Groove™ Technology

improves water evacuation and helps increase resistance to hydroplaning<sup>1</sup>

#### Improved Wet Rubber Compound and Tread Design

provides 20% shorter stopping distance on wet roads as compared to the previous generation Firestone Firehawk Wide Oval Indy 500 tire

#### New Tread Compound and Wide Shoulder Blocks

provide impressive handling and cornering in dry conditions<sup>1</sup>

<sup>1</sup>As compared to the prior generation Firestone Firehawk Wide Oval Indy 500.

# Firestone



# FIREHAWK™ INDY 500®

### Top Fitments

- Ford Mustang
- Nissan 350Z
- Dodge Challenger
- Pontiac GTO

### Warranty\*

- Gold Pledge Limited Warranty
- 90-Day Buy & Try™ Guarantee



## GOLD PLEDGE

### Tire Specifications

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Widths	Measuring Widths	Overall Diameter	Overall Width	Tread Revs (32nd)	UTQG	WT
-----------------------------------	------------	-------------	------------------	-----------------	------------------	------------------	---------------	-------------------	------	----

16" Rim Diameter											
195/65R16 87W		009332	BW	5.5-7.0	6.0	24.4	7.9	9	853	340AA	19
205/65R16 91W		011969	BW	5.5-7.5	6.5	24.9	8.4	9	837	340AA	21
205/65R16 97W		011986	BW	5.5-7.5	6.5	24.1	8.4	9	865	340AA	21
225/65R16 92W		012003	BW	6.0-8.0	7.0	24.9	9.2	9	837	340AA	23
265/65R16 97W	XL	012020	BW	6.5-7.5	7.0	25.2	8.1	9	897	340AA	20

17" Rim Diameter											
215/65R17 94W		004352	BW	6.0-7.5	7.0	26.3	8.9	10	792	340AA	24
225/65R17 97W		009331	BW	6.0-8.0	7.0	26.8	9.2	10	778	340AA	25
235/65R17 99W		009330	BW	6.5-8.5	7.5	27.2	9.7	10	767	340AA	26
205/65R17 93W	XL	012037	BW	5.5-7.5	6.5	25.1	8.4	9	829	340AA	22
225/65R17 94W		012054	BW	6.0-8.0	7.0	25.9	9.2	10	804	340AA	24
245/65R17 96W		009329	BW	6.5-8.5	7.5	26.3	9.7	10	782	340AA	25
265/65R17 97W	XL	012071	BW	6.5-7.5	7.0	24.3	8.1	9	859	340AA	22
215/65R17 98W	XL	012105	BW	7.0-8.5	7.5	25.0	8.9	10	835	340AA	23
235/65R17 99W	XL	012139	BW	7.5-9.0	8.0	25.4	9.3	10	822	340AA	23
245/65R17 99W	XL	012156	BW	7.5-9.0	8.0	25.7	9.6	10	812	340AA	25
265/65R17 94W	XL	012190	BW	7.0-8.0	7.5	23.5	8.4	9	888	340AA	20
285/65R17 97W		012207	BW	8.0-9.5	8.5	24.7	9.8	10	843	340AA	25
285/65R17 99W		012224	BW	8.5-10.0	9.0	25.0	10.2	10	832	340AA	25
275/65R17 99W		004354	BW	9.0-11.0	9.5	25.7	10.9	10	812	340AA	28

18" Rim Diameter											
235/65R18 100W		004350	BW	6.5-8.5	7.5	28.2	9.7	10	740	340AA	28
245/65R18 95W		012241	BW	6.0-8.0	7.0	26.9	9.2	10	775	340AA	26
225/65R18 101W	XL	009328	BW	6.5-8.5	7.5	27.3	9.7	10	764	340AA	28
215/65R18 93W	XL	012288	BW	7.0-8.0	7.0	25.6	8.4	9	813	340AA	23
225/65R18 95W	XL	012275	BW	7.0-8.5	7.5	25.9	8.9	10	803	340AA	24
235/65R18 96W	XL	012292	BW	7.5-9.0	8.0	26.3	9.3	9	791	340AA	26
245/65R18 100W	XL	012309	BW	7.5-9.0	8.0	26.7	9.6	10	782	340AA	27
255/65R18 103W	XL	011952	BW	8.0-9.5	8.5	27.1	10.0	10	770	340AA	28
215/65R18 99W	XL	012326	BW	7.0-8.5	7.5	24.8	8.6	9	841	340AA	23
225/65R18 92W	XL	012380	BW	7.5-8.0	8.0	25.1	9.1	10	831	340AA	23
235/65R18 95W	XL	012377	BW	8.0-9.5	8.5	25.4	9.5	10	820	340AA	24
245/65R18 97W	XL	012394	BW	8.0-9.5	8.5	25.7	9.6	10	810	340AA	26
255/65R18 99W	XL	012411	BW	8.5-10.0	9.0	26.0	10.2	10	801	340AA	27
275/65R18 99W		009327	BW	9.0-11.0	9.5	26.7	10.9	10	782	340AA	28
245/65R18 92W	XL	012428	BW	8.0-9.5	8.5	24.8	9.8	10	841	340AA	24
255/65R18 94W	XL	012445	BW	8.5-10.0	9.0	25.0	10.2	10	833	340AA	25
265/65R18 97W	XL	012462	BW	9.0-10.5	9.5	25.3	10.7	10	823	340AA	26
275/65R18 95W		012496	BW	9.0-11.0	9.5	25.6	10.9	10	815	340AA	27

Firestone Tire.com | © 2024 Bridgestone Americas Tire Operations, LLC.

Rev: 1/2024 EN

# Firestone

### Tire Specifications Legend

- △ B-Silent
- \* OEM Tire
- ✱ MOE (Mercedes Exclusive)
- ∧ RFT (Run Flat Tire)
- BW Blackwall
- OML Outline White Letter
- XL Extra Load (XL)
- ~ Pinned for #12 Stud Sizes
- f Pinned for #15 Stud Sizes
- \*\* Pinned for #16 Stud Sizes
- \*\*\* Pinned for #17 Stud Sizes

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Widths	Measuring Widths	Overall Diameter	Overall Width	Tread Revs (32nd)	UTQG	WT
-----------------------------------	------------	-------------	------------------	-----------------	------------------	------------------	---------------	-------------------	------	----

16" Rim Diameter											
225/65R19 104W	XL	002926	BW	7.0-8.5	7.5	28.7	10.0	10	728	340AA	30
245/65R19 96W	XL	012530	BW	7.0-8.5	7.5	27.0	8.9	10	772	340AA	28
245/65R19 98W	XL	012547	BW	7.5-9.0	8.0	27.7	9.6	10	753	340AA	27
225/65R19 93W	XL	012581	BW	7.5-9.0	8.0	26.1	9.1	10	798	340AA	25
245/65R19 98W	XL	012588	BW	8.0-9.5	8.5	28.7	9.8	10	779	340AA	27
265/65R19 100W	XL	012615	BW	8.5-10.0	9.0	27.1	10.2	10	770	340AA	28
275/65R19 101W		002925	BW	9.0-10.5	9.5	27.4	10.7	10	760	340AA	28
225/65R19 88W	XL	012632	BW	9.0-11.0	9.5	27.7	10.9	10	753	340AA	29
235/65R19 91W	XL	012649	BW	7.5-9.0	8.0	25.2	9.1	10	825	340AA	24
245/65R19 93W	XL	012666	BW	8.0-9.5	8.5	25.5	9.5	10	818	340AA	25
245/65R19 93W	XL	012683	BW	8.0-9.5	8.5	25.8	9.8	10	808	340AA	26
255/65R19 96W	XL	012700	BW	8.5-10.0	9.0	26.0	10.2	10	801	340AA	28
265/65R19 96W	XL	012717	BW	9.0-10.5	9.5	26.3	10.7	10	791	340AA	29
275/65R19 100W	XL	012751	BW	9.0-11.0	9.5	26.6	10.9	10	784	340AA	30
285/65R19 99W	XL	003280	BW	9.5-11.0	10.0	26.9	11.4	10	775	340AA	30
265/65R19 93W	XL	012802	BW	9.0-10.0	9.5	25.3	10.7	10	823	340AA	27
275/65R19 96W	XL	012819	BW	9.0-10.0	9.5	25.6	10.9	10	815	340AA	28
285/65R19 98W	XL	012836	BW	9.5-10.5	10.0	25.8	11.4	10	808	340AA	30
325/30R19 101W		002924	BW	11.0-12.0	11.5	26.7	13.0	10	778	340AA	33

20" Rim Diameter											
245/65R20 103W	XL	012853	BW	7.5-9.0	8.0	28.7	9.6	10	727	340AA	29
255/65R20 101W	XL	012870	BW	8.0-9.5	8.5	29.1	10.0	10	717	340AA	30
245/65R20 99W	XL	012887	BW	8.0-9.5	8.5	27.7	9.8	10	751	340AA	28
275/65R20 108W	XL	012921	BW	9.0-11.0	9.5	28.7	10.9	10	727	340AA	32
285/65R20 97W	XL	012938	BW	8.5-10.0	9.0	27.0	10.2	10	771	340AA	29
275/65R20 102W	XL	012972	BW	9.0-11.0	9.5	27.6	10.9	10	756	340AA	31
285/65R20 100W		002922	BW	9.5-11.0	10.0	27.9	11.4	10	747	340AA	31
305/65R20 104W		002921	BW	10.0-12.0	11.0	28.4	12.3	10	733	340AA	34
285/65R20 99W	XL	012989	BW	9.5-10.5	10.0	26.8	11.4	10	778	340AA	32
285/65R20 101W	XL	004351	BW	10.0-11.0	10.5	27.0	11.9	10	772	340AA	33

† Conditions apply. See FirestoneTire.com/warranty for details.

# FIREHAWK™ AS V2

ALL-SEASON, ULTRA-HIGH PERFORMANCE



## FOR EXCITING SPORTY PERFORMANCE

### Features & Benefits



Impressive dry handling for sporty grip and responsive handling



Excellent wet performance and handling



Stops shorter in snow<sup>1</sup>

50,000

MILE LIMITED WARRANTY\*

80,000

KILOMETRE LIMITED WARRANTY\*



#### IndyCar Inspired Tread Design

ensures confident wet handling with a tread inspired by the Firestone INDYCAR Firehawk rain race tire

#### Interlocking Lugs

help provide confident wet handling

#### Large Outboard Tread Blocks

supported by circumferential grooves and open shoulder slots provide hydroplaning resistance

#### 3D Full-Depth Sipes

provide excellent snow performance throughout the life of the tire

<sup>†</sup> Conditions apply. See [FirestoneTire.com/warranty](http://FirestoneTire.com/warranty) for details.  
<sup>1</sup> Comparison based on the Firestone Firehawk AS V2 tires vs. the General G-MAX™ AS05 tires from internal testing. Results may vary depending on proper tire and vehicle maintenance, road conditions, and driving habits.

# Firestone



# FIREHAWK™ AS V2

## Top Fitments

Chevrolet Camaro, Chevrolet Equinox,  
 Dodge Challenger, Dodge Charger,  
 Ford Escape, Ford Fusion,  
 Ford Mustang, Honda Accord,  
 Honda Civic, Honda CR-V,  
 Nissan Altima, Toyota Camry,  
 Toyota Corolla, Toyota RAV4

## Warranty\*

- 50,000 Mile Limited Warranty
- Gold Pledge Limited Warranty
- 90-Day Buy & Try™ Guarantee



Scan to discover more



## Tire Specifications Legend

- △ B-Silent
- \* OEM Tire
- ✚ MOE (Mercedes Exclusive)
- ∧ RFT (Run Flat Tire)
- BW Blackwall
- OWL Outline White Letter
- XL Extra Load (XL)
- ~ Pinned for #12 Stud Sizes
- f Pinned for #15 Stud Sizes
- \*\* Pinned for #16 Stud Sizes
- \*\*\* Pinned for #17 Stud Sizes

## Tire Specifications

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Section Width	Tread Depth (32nd)	Revs Per Mile	UTQG	Wt
17" Rim Diameter											
215/65R17 99H		014736	BW	-	8.7	28.0	28.0	9	743	500 A.A.	26
225/60R17 99V		008279	BW	6.0-8.0	6.5	27.6	9.0	9	754	500 A.A.	24
215/55R17 94V		008230	BW	6.0-7.5	7.0	26.3	8.9	10	792	500 A.A.	21
225/55R17 97V		008243	BW	6.0-8.0	7.0	26.8	9.2	9	778	500 A.A.	23
235/55R17 99W		008255	BW	6.5-8.5	7.5	27.2	9.7	9	767	500 A.A.	26
205/50R17 93V	XL	008249	BW	5.5-7.5	6.5	25.1	8.4	9	829	500 A.A.	23
215/50R17 95W	XL	008236	BW	6.0-7.5	7.0	25.5	8.9	9	817	500 A.A.	24
225/50R17 98W	XL	008235	BW	6.0-8.0	7.0	25.9	9.2	9	804	500 A.A.	24
235/50R17 96V	XL	008264	BW	6.5-8.5	7.5	26.3	9.7	9	792	500 A.A.	26
215/45R17 91W	XL	008241	BW	7.0-8.0	7.0	24.7	8.4	9	845	500 A.A.	23
225/45R17 94W	XL	008245	BW	7.0-8.5	7.5	25.0	8.9	9	835	500 A.A.	24
235/45R17 97W	XL	008270	BW	7.5-9.0	8.0	25.4	9.3	9	822	500 A.A.	26
245/45R17 99W	XL	008278	BW	7.5-9.0	8.0	25.7	9.6	9	812	500 A.A.	28

## 18" Rim Diameter

225/60R18 100V		008288	BW	6.0-8.0	6.5	28.6	9.0	9	728	500 A.A.	27
235/60R18 103V		013407	BW	6.5-8.5	7.0	29.1	9.5	9	716	500 A.A.	27
215/55R18 95H		008281	BW	6.0-7.5	7.0	27.3	8.9	9	764	500 A.A.	23
225/55R18 98V		013406	BW	6.0-8.0	7.0	27.8	9.2	8	749	500 A.A.	25
235/55R18 100V		008281	BW	6.5-8.5	7.5	28.2	9.7	9	740	500 A.A.	27
245/55R18 103W		013409	BW	7.0-8.5	7.5	28.6	10.0	9	728	500 A.A.	27
225/50R18 95W		008253	BW	6.0-8.0	7.0	26.9	9.2	9	775	500 A.A.	24
235/50R18 97W		008250	BW	6.5-8.5	7.5	27.3	9.7	9	764	500 A.A.	24
245/50R18 100W		013408	BW	7.0-8.5	7.5	27.7	10.0	9	753	500 A.A.	27
215/45R18 93W	XL	012036	BW	7.0-8.0	7.0	25.6	8.4	9	813	500 A.A.	24
225/45R18 95W	XL	008248	BW	7.0-8.5	7.5	25.9	8.9	9	803	500 A.A.	25
235/45R18 94W	XL	008240	BW	7.5-9.0	8.0	26.3	9.3	9	791	500 A.A.	25
245/45R18 100W	XL	008251	BW	7.5-9.0	8.0	26.7	9.6	9	782	500 A.A.	29
255/45R18 99W		014375	BW	-	-	-	-	-	-	500 A.A.	26
225/40R18 92W	XL	008234	BW	7.5-9.0	8.0	25.1	9.1	9	831	500 A.A.	24
235/40R18 95W	XL	008260	BW	8.0-9.5	8.5	25.4	9.5	9	820	500 A.A.	26
245/40R18 97W	XL	008275	BW	8.0-9.5	8.5	25.7	9.8	9	810	500 A.A.	26
255/35R18 94Y	XL	014374	BW	-	-	-	-	-	-	500 A.A.	26

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Rim Diameter	Section Width	Tread Depth (32nd)	Revs Per Mile	UTQG	Wt
-----------------------------------	------------	-------------	------------------	---------------------	----------------------	----------------------	---------------	--------------------	---------------	------	----

## 19" Rim Diameter

225/55R19 99V		013415	BW	6.0-8.0	7.0	28.8	9.2	9	724	500 A.A.	25
235/55R19 105W	XL	013416	BW	6.5-8.5	7.5	29.2	9.7	9	714	500 A.A.	29
225/45R19 96W	XL	012039	BW	7.0-8.5	7.5	27.0	8.9	9	772	500 A.A.	27
245/45R19 98W		008259	BW	7.5-9.0	8.0	27.7	9.6	9	753	500 A.A.	27
225/40R19 93Y	XL	014377	BW	-	-	-	-	-	-	500 A.A.	25
235/40R19 96W	XL	008258	BW	8.0-9.5	8.5	26.4	9.5	9	788	500 A.A.	26
245/40R19 98W	XL	008262	BW	8.0-9.5	8.5	26.7	9.8	9	779	500 A.A.	28
255/40R19 100W	XL	011597	BW	8.5-10.0	9.0	27.1	10.2	9	770	500 A.A.	29
255/35R19 96Y	XL	014378	BW	-	-	-	-	-	-	500 A.A.	27

## 20" Rim Diameter

235/55R20 102W		013419	BW	6.5-8.5	7.5	30.2	9.7	9	691	500 A.A.	29
245/50R20 102V		013420	BW	7.0-8.5	7.5	29.7	10.0	9	702	500 A.A.	29
265/50R20 107V		013422	BW	7.5-9.5	8.5	30.5	10.9	9	684	500 A.A.	35
245/45R20 103W	XL	008256	BW	7.5-9.0	8.0	28.7	9.6	9	727	500 A.A.	31
255/45R20 99W	XL	012041	BW	8.0-9.5	8.5	29.1	10.0	9	717	500 A.A.	32
275/40R20 108W	XL	008276	BW	9.0-11.0	9.5	28.7	10.9	9	727	500 A.A.	33
265/35R20 99Y	XL	014380	BW	-	-	-	-	-	-	500 A.A.	31



# WEATHERGRIP™

TOURING



## FOR COMMANDING THE ROAD - RAIN, SNOW AND SHINE

### Features & Benefits



Confident wet performance year round



Long-lasting performance with a 65,000 mile limited warranty<sup>†</sup>



Quiet and comfortable ride




3-Peak Mountain Snowflake Certified

**65,000**

MILE LIMITED WARRANTY\*

**105000**

KILOMETRE LIMITED WARRANTY\*



**Open Shoulder Slots**  
for enhanced water evacuation from contact patch<sup>1</sup>

**3D Full-Depth Sipes**  
on ALL ribs for even wear throughout the tire's limited mileage warranty period and for enhanced snow traction<sup>1</sup>

**Snow Traction Claw™ Technology**  
on center and shoulder blocks with snow vices on intermediate ribs

<sup>†</sup> Conditions apply. See FirestoneTire.com/warranty for details.  
<sup>1</sup> Based on internal testing on a closed course using a Toyota Camry and the GoodYear Assurance® WeatherReady™ tire in size 215/55R17, the Michelin® CrossClimate™ tire in size 215/55R17, and the Firestone WeatherGrip™ tire in size 215/55R17. Actual results on road may vary.

**Firestone**



# WEATHERGRIP™

## Top Fitments

- Honda Accord
- Toyota Camry
- Nissan Altima
- Honda Civic
- Toyota Corolla
- Honda CR-V

## Warranty\*

- 65,000 Mile Limited Warranty
- Gold Pledge Limited Warranty
- 90-Day Buy & Try™ Guarantee



## Tire Specifications

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Widths	Measuring Widths	Overall Diameter	Overall Width	Tread Depth (32nd)	Revs Mile	UTQG	WR
-----------------------------------	------------	-------------	------------------	-----------------	------------------	------------------	---------------	--------------------	-----------	------	----

<b>15" Rim Diameter</b>											
205/50R15 98T		011519	BW	5.0-7.0	6.0	26.3	8.2	10	791	640AA	22
215/50R15 98H		004419	BW	5.5-7.0	6.5	26.9	8.7	10	775	640AA	21
175/65R15 94H		011548	BW	5.0-6.0	5.0	24.0	7.0	10	889	640AA	17
185/65R15 94H		011515	BW	5.0-6.5	5.5	24.5	7.4	10	852	640AA	17
195/65R15 91H		004405	BW	5.5-7.0	6.0	25.0	7.9	10	833	640AA	18
205/65R15 94H	XL	004417	BW	5.5-7.5	6.0	25.5	8.2	10	818	640AA	20
185/65R15 94H		011526	BW	5.0-6.5	5.5	23.7	7.4	10	878	640AA	19
195/65R15 94H		004409	BW	5.5-7.0	6.0	24.2	7.9	10	860	640AA	19
185/65R15 92V		011549	BW	5.0-6.5	6.0	23.0	7.6	10	905	640AA	19

<b>16" Rim Diameter</b>											
215/70R16 100H		009164	BW	5.5-7.0	6.5	27.9	8.7	10	747	640AA	22
235/70R16 106H		009171	BW	6.0-8.0	7.0	29.0	9.5	10	719	640AA	21
205/65R16 98H		004415	BW	5.5-7.5	6.0	26.5	8.2	10	787	640AA	21
215/65R16 98H		004421	BW	6.0-7.5	6.5	27.0	8.7	10	771	640AA	22
225/65R16 103T		011533	BW	6.0-8.0	6.5	27.5	9.0	10	758	640AA	22
205/60R16 92V		011531	BW	6.0-8.5	7.0	28.0	9.5	10	743	640AA	25
205/60R16 92V		011507	BW	5.5-7.5	6.0	25.7	8.2	10	812	640AA	20
215/60R16 95V		011517	BW	6.0-8.0	6.5	26.1	8.7	10	797	640AA	21
225/60R16 98V		011525	BW	6.0-8.0	6.5	26.6	9.0	10	783	640AA	24
235/60R16 100H		011542	BW	6.5-8.5	7.0	27.1	9.5	10	769	640AA	26
185/65R16 93H		011562	BW	5.0-6.5	6.0	24.0	7.6	10	867	640AA	19
195/65R16 93V		011536	BW	5.5-7.0	6.0	24.4	7.9	10	853	640AA	20
205/65R16 91V		011598	BW	5.5-7.5	6.5	24.9	8.4	10	837	640AA	19
215/65R16 93H		009100	BW	6.0-7.5	7.0	25.3	8.9	10	824	640AA	19
195/50R16 64V		011550	BW	5.5-7.0	6.0	23.7	7.9	10	879	640AA	20

<b>17" Rim Diameter</b>											
215/65R17 99H		009170	BW	6.0-7.5	6.5	28.0	8.7	10	743	640AA	23
225/65R17 102H		004427	BW	6.0-8.0	6.5	28.5	9.0	10	731	640AA	24
235/65R17 104H		008101	BW	6.5-8.5	7.0	29.1	9.5	10	717	640AA	27
215/60R17 98H		011507	BW	6.0-7.5	6.5	27.2	8.7	10	767	640AA	23
225/60R17 98H		004431	BW	6.0-8.0	6.5	27.6	9.0	10	754	640AA	25
235/60R17 102H		011535	BW	6.5-8.5	7.0	28.1	9.5	10	741	640AA	24
215/55R17 94V		011534	BW	6.0-7.5	7.0	26.3	8.9	10	792	640AA	22
225/55R17 97V		011546	BW	6.0-8.0	7.0	26.8	9.2	10	778	640AA	22
235/55R17 99V		011920	BW	6.5-8.5	7.5	27.2	9.7	10	767	640AA	25
205/60R17 93V	XL	011532	BW	5.5-7.5	6.5	25.1	8.4	10	829	640AA	23
215/60R17 95V	XL	011538	BW	6.0-7.5	7.0	25.5	8.9	10	817	640AA	24
225/60R17 94V		011551	BW	6.0-8.0	7.0	25.9	9.2	10	804	640AA	23
235/60R17 96V		011500	BW	6.5-8.5	7.5	26.3	9.7	10	792	640AA	25
215/45R17 91V	XL	011541	BW	7.0-8.0	7.0	24.7	8.4	10	845	640AA	22
225/45R17 91V		011553	BW	7.0-8.5	7.5	25.0	8.9	10	835	640AA	22

Firestone Tire.com | © 2024 Bridgestone Americas Tire Operations, LLC.

Rev: 1/2024 EN

## Tire Specifications Legend

△ B-Silent	BW Blackwall	~ Pinned for #12 Stud Sizes
* OEM Tire	OML Outline White Letter	f Pinned for #15 Stud Sizes
⌘ MOE (Mercedes Exclusive)	XL Extra Load (XL)	** Pinned for #16 Stud Sizes
∧ RTT (Run Flat Tire)	◆ Pinned for #11 Stud Sizes	*** Pinned for #17 Stud Sizes

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Widths	Measuring Widths	Overall Diameter	Overall Width	Tread Depth (32nd)	Revs Mile	UTQG	WR
-----------------------------------	------------	-------------	------------------	-----------------	------------------	------------------	---------------	--------------------	-----------	------	----

<b>18" Rim Diameter</b>											
235/65R18 109H		009167	BW	6.5-8.5	7.0	30.0	9.5	10	683	640AA	28
225/65R18 100H		009169	BW	6.0-9.0	6.5	28.6	9.0	10	728	640AA	24
235/60R18 103H		009163	BW	6.5-8.5	7.0	29.1	9.5	10	716	640AA	25
245/60R18 105H		009166	BW	7.0-8.5	7.0	29.6	9.8	10	704	640AA	30
215/65R18 95H		011557	BW	6.0-7.5	7.0	27.3	8.9	10	784	640AA	23
225/65R18 98V		011544	BW	6.0-8.0	7.0	27.8	9.2	10	749	640AA	25
235/65R18 100V		011563	BW	6.5-8.5	7.5	28.2	9.7	10	740	640AA	25
225/65R18 95H		011521	BW	6.0-8.0	7.0	26.9	9.2	10	775	640AA	24
225/65R18 97V		009165	BW	6.5-8.5	7.5	27.3	9.7	10	764	640AA	24
225/65R18 95V	XL	011566	BW	7.0-8.5	7.5	25.9	8.9	10	803	640AA	25
235/65R18 96V		011558	BW	7.5-9.0	8.0	26.3	9.3	10	791	640AA	23
245/65R18 100V	XL	015686	BW	7.5-9.0	8.0	26.7	9.6	10	782	640AA	25

<b>19" Rim Diameter</b>											
235/65R19 101H		009168	BW	6.5-8.5	7.5	29.2	9.7	10	714	640AA	25
225/65R19 96V	XL	011562	BW	8.0-9.5	8.5	26.4	9.5	10	788	640AA	27

† Conditions apply. See FirestoneTire.com/warranty for details.

# FR710™

ALL-SEASON TOURING



## SOLID PERFORMANCE WITHIN REACH

### FEATURES AND BENEFITS



All-season performance



Up to 65,000 mile limited warranty\*



Quiet, comfortable ride


UP TO

**65,000**

MILE LIMITED WARRANTY\*

**105,000**

KILOMETRE LIMITED WARRANTY\*



#### Long-Lasting Tread Compound

offers up to a 65,000 mile limited warranty\*

#### Circumferential Grooves

help channel water out of the footprint area to resist hydroplaning

#### All-Season Tread Design

contributes to ride comfort

\* Excludes certain sizes. See FirestoneTire.com/warranty for details.

# Firestone



# FR710™



### Top Fitments

- Toyota Sienna
- 65,000 Mile Limited Warranty (P-Metric sizes only)
- Gold Pledge Limited Warranty
- 90-Day Buy & Try™ Guarantee

### Warranty\*



**GOLD PLEDGE**

### Tire Specifications

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd)	Revs Per Mile	UTOG	WT
<b>15" Rim Diameter</b>											
P185/65R15 86H *		003192	BW	5.0-6.5	5.5	24.5	7.4	10	852	500 A.B	17
P185/60R15 84H *		007278	BW	5.0-6.5	5.5	23.7	7.4	10	878	560 A.A	17
<b>17" Rim Diameter</b>											
P235/60R17 100T*		006505	BW	6.5-8.5	7.0	28.1	9.5	10	741	560 A.B	27
<b>18" Rim Diameter</b>											
P225/60R18 99T*		134037	BW	6.0-8.0	6.5	28.6	9.0	11	728	520 A.B	26

### Tire Specifications Legend

Δ	B-Silent	BW	Blackwall	~	Pinned for #12 Stud Sizes
*	OEM Tire	OWL	Outline White Letter	f	Pinned for #15 Stud Sizes
‡	MOE (Mercedes Exclusive)	XL	Extra Load (XL)	**	Pinned for #16 Stud Sizes
^	RFT (Run Flat Tire)	◆	Pinned for #11 Stud Sizes	***	Pinned for #17 Stud Sizes



# FT140™

TOURING



## SMOOTH, QUIET RIDE IN BOTH WET AND DRY ROAD CONDITIONS

### FEATURES AND BENEFITS



Quiet, comfortable ride




Confident wet performance



All-season performance



Engineered specifically to compliment  
your vehicle as Original Equipment



#### Tread Pattern

tuned for a quiet ride

#### Pattern Features

designed to provide all-season  
performance

#### Tread Compound

formulated for dependable  
handling and braking  
performance

# Firestone



### Top Fitments

- Chevrolet Malibu
- Nissan Sentra
- Honda Civic
- Toyota Corolla
- Toyota Camry

### Warranty\*

- Gold Pledge Limited Warranty
- 90-Day Buy & Try™ Guarantee



### Tire Specifications

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd)	Revs Per Mile	UTOG	WT
<b>15" Rim Diameter</b>											
195/65R15 91S *		006515	BW	5.5-7.0	6.0	25.0	7.9	10	833	560 A.A.	17
<b>16" Rim Diameter</b>											
P205/65R16 94H *		003196	BW	5.5-7.5	6.0	26.5	8.2	10	787	560 A.A.	31
205/65R16 95H *		003208	BW	5.5-7.5	6.0	26.5	8.2	10	787	560 A.A.	20
205/60R16 92H *		007221	BW	5.5-7.5	6.0	25.7	8.2	10	812	560 A.A.	20
205/60R16 92H *		008622	BW	5.5-7.5	6.0	25.7	8.2	10	812	560 A.A.	19
205/55R16 91H *		006518	BW	5.5-7.5	6.5	24.9	8.4	10	837	560 A.A.	18
P205/55R16 89H *		007148	BW	5.5-7.5	6.5	24.9	8.4	10	837	560 A.A.	19
205/55R16 91V *		015149	BW	-	-	-	-	9	-	560 A.A.	18
215/55R16 93H *		021285	BW	6.0-7.5	7.0	25.3	8.9	10	824	560 A.A.	21
<b>17" Rim Diameter</b>											
P235/65R17 103T *		003213	BW	6.5-8.5	7.0	29.1	9.5	10	717	560 A.A.	28
205/55R17 91V *		007222	BW	5.5-7.5	6.5	25.9	8.4	10	804	560 A.A.	20
205/50R17 89V *		000980	BW	5.5-7.5	6.5	25.1	8.4	10	829	560 A.A.	21
205/50R17 89V *		015150	BW	-	-	-	-	9	-	560 A.A.	19
215/50R17 91H *		000285	BW	8.0-7.5	7.0	25.5	8.9	11	817	560 A.A.	22

### Tire Specifications Legend

△ B-Silent	BW Blackwall	~ Pinned for #12 Stud Sizes
* OEM Tire	OWL Outline White Letter	f Pinned for #15 Stud Sizes
¥ MOE (Mercedes Exclusive)	XL Extra Load (XL)	** Pinned for #16 Stud Sizes
^ RFT (Run Flat Tire)	◆ Pinned for #11 Stud Sizes	*** Pinned for #17 Stud Sizes

# ALL SEASON

ALL-SEASON



## A QUALITY TIRE AT A GREAT VALUE FROM A BRAND YOU CAN TRUST

### Features & Benefits



A tire you can count on



All-season performance



Built to last


UP TO

**65,000**

MILE LIMITED WARRANTY\*

**105,000**

KILOMETRE LIMITED WARRANTY\*



#### Deep Sipes

retain wet and all-season performance

#### Tread Design

built to provide performance in wet, dry, and snowy conditions with traction and handling all year long

\* 65,000 mile, 90,000 kilometre limited warranty (CUV/Intended Sizes), 65,000 mile, 105,000 kilometre limited warranty (All Other Sizes). Conditions apply. See [FirestoneTire.com/warranty](http://FirestoneTire.com/warranty) for details.

# Firestone

# ALL SEASON



## Top Fitments

- Toyota Corolla
- Dodge Caravan
- Honda CR-V

## Warranty\*

- 55,000 Mile Limited Warranty (CUV Intended Sizes)
- 65,000 Mile Limited Warranty (All Other Sizes)
- Gold Pledge Limited Warranty
- 90-Day Buy & Try™ Guarantee



## Tire Specifications

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Widths	Measuring Widths	Overall Diameter	Overall Width	UTQG	Wt
-----------------------------------	------------	-------------	------------------	-----------------	------------------	------------------	---------------	------	----

14" Rim Diameter											
185/65R14 91T		004092	BW	5.0-6.5	6.0	24.6	7.9	11	840	580 A.B	16
185/65R14 98T		004040	BW	5.0-6.5	5.5	23.5	7.4	10	868	580 A.B	17
15" Rim Diameter											
205/65R15 98T		004044	BW	5.0-7.0	6.0	26.3	8.2	10	791	580 A.B	19
205/65R15 98T		004014	BW	5.5-7.0	6.5	26.9	8.7	10	775	580 A.B	21
205/65R15 98T		004054	BW	5.0-6.0	5.0	24.0	7.0	10	869	580 A.B	15
185/65R15 98T		004018	BW	5.0-6.5	5.5	24.5	7.4	10	862	580 A.B	16
185/65R15 91T		006252	BW	5.5-7.0	6.0	25.0	7.9	10	833	580 A.B	17
185/65R15 91H		013746	BW	5.5-7.0	6.0	26.0	7.9	10	853	580 A.B	19
205/65R15 94T		004012	BW	5.5-7.5	6.0	26.5	8.2	9	818	580 A.B	18
185/65R15 94T		004098	BW	5.0-6.5	5.5	23.7	7.4	10	878	580 A.B	15
185/65R15 98T		006254	BW	5.5-7.0	6.0	24.2	7.9	10	860	580 A.B	17

16" Rim Diameter											
215/70R16 100S		003036	BW	5.5-7.0	6.5	27.9	8.7	10	747	480 A.B	22
215/70R16 103T		003042	BW	6.0-7.5	6.5	28.4	9.0	10	733	480 A.B	24
205/70R16 104T		003024	BW	6.0-8.0	7.0	29.0	9.5	10	719	480 A.B	26
205/65R16 98T		004030	BW	5.5-7.5	6.0	26.5	8.2	9	771	580 A.B	19
215/65R16 98T		004020	BW	6.0-7.5	6.5	27.0	8.7	9	797	580 A.B	23
205/65R16 100T		004046	BW	6.0-8.0	6.5	27.5	9.0	10	758	580 A.B	23
205/65R16 103T		004026	BW	6.5-8.5	7.0	29.0	9.5	10	743	580 A.B	27
205/65R16 102T		006258	BW	5.5-7.5	6.0	25.7	8.2	9	812	580 A.B	18
215/65R16 95T		003816	BW	6.0-7.5	6.5	26.1	8.7	9	797	580 A.B	20
215/65R16 95V		013747	BW	6.0-7.5	6.5	26.1	8.7	9	797	580 A.B	20
205/65R16 98T		004002	BW	6.0-8.0	6.5	26.6	9.0	10	793	580 A.B	25
205/65R16 100T		004098	BW	6.5-8.5	7.0	27.1	9.5	10	769	580 A.B	25
185/55R16 93T		003051	BW	5.0-6.5	6.0	24.0	7.6	10	867	580 A.B	17
205/55R16 91H		013749	BW	5.5-7.5	6.5	24.9	8.4	9	837	580 A.B	18
215/55R16 93T		004042	BW	6.0-7.5	7.0	25.3	8.9	9	824	580 A.B	19
205/65R16 97H		004070	BW	5.5-7.5	6.5	24.1	8.4	9	865	580 A.B	19

17" Rim Diameter											
215/65R17 98T		004050	BW	6.0-7.5	6.5	28.0	8.7	9	743	580 A.B	22
225/65R17 102H		013343	BW	6.0-8.0	6.5	28.5	9.0	10	731	480 A.B	24
205/65R17 104T		003034	BW	6.5-8.5	7.0	29.1	9.5	10	717	480 A.B	26
215/65R17 98T		004634	BW	6.0-7.5	6.5	27.2	8.7	9	767	580 A.B	20
225/65R17 99T		004022	BW	6.0-8.0	6.5	27.8	9.0	10	754	580 A.B	22
225/65R17 102T		004052	BW	6.5-8.5	7.0	28.1	9.5	10	741	580 A.B	24
215/65R17 94V		013750	BW	6.0-7.5	7.0	26.3	8.9	9	792	580 A.B	20
225/65R17 97T		006255	BW	6.0-8.0	7.0	26.8	9.2	10	778	580 A.B	21
205/55R17 98T		006296	BW	6.5-8.5	7.5	27.2	9.7	10	767	580 A.B	23
205/55R17 99H		007790	BW	5.5-7.5	6.5	25.1	8.4	9	829	580 A.B	21
215/55R17 91H		007789	BW	6.0-7.5	7.0	25.5	8.9	9	817	580 A.B	21
225/55R17 94T		006293	BW	6.0-8.0	7.0	25.9	9.2	10	804	580 A.B	20

## Tire Specifications Legend

- △ B-Silent
- \* OEM Tire
- ✱ MOE (Mercedes Exclusive)
- ∧ RFT (Run Flat Tire)
- ~ Pinned for #12 Stud Sizes
- f Pinned for #15 Stud Sizes
- \*\* Pinned for #16 Stud Sizes
- \*\*\* Pinned for #17 Stud Sizes

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Widths	Measuring Widths	Overall Diameter	Overall Width	UTQG	Wt
-----------------------------------	------------	-------------	------------------	-----------------	------------------	------------------	---------------	------	----

18" Rim Diameter											
235/65R18 106H		013761	BW	6.5-8.5	7.0	30.0	9.5	10	683	480 A.B	29
225/65R18 106S		003072	BW	7.0-9.0	7.5	31.1	10.2	10	671	480 A.B	31
225/65R18 100T		004680	BW	6.0-8.0	6.5	28.6	9.0	10	728	500 A.B	23
245/65R18 103H		003040	BW	7.0-8.5	7.0	29.1	9.5	10	716	480 A.B	25
245/65R18 105H		013342	BW	7.0-8.5	7.0	29.6	9.8	10	704	480 A.B	30
225/65R18 98H		003058	BW	7.5-9.5	8.0	30.5	10.7	10	683	480 A.B	32
225/65R18 100H		003076	BW	6.0-8.0	7.0	27.8	9.2	10	749	480 A.B	23
235/65R18 100H		003030	BW	6.5-8.5	7.5	28.2	9.7	10	740	480 A.B	24
245/65R18 103T		003067	BW	7.0-8.5	7.5	28.6	10.0	10	728	500 A.B	25
235/45R18 94V		013745	BW	7.5-9.0	8.0	26.3	9.3	10	791	500 A.B	24

19" Rim Diameter											
225/65R19 108S		003084	BW	7.0-9.0	7.5	31.1	10.2	10	671	480 A.B	32
235/65R19 101H		003050	BW	6.5-8.5	7.5	29.2	9.7	10	714	480 A.B	25
245/65R19 103S		003080	BW	7.0-8.5	7.5	29.7	10.0	10	703	480 A.B	26

20" Rim Diameter											
225/65R20 107H		003092	BW	7.0-9.0	8.0	31.0	10.4	10	672	480 A.B	30
245/65R20 102H		003082	BW	7.0-8.5	7.5	29.7	10.0	10	702	480 A.B	27

\* Conditions apply. See FirestoneTire.com/warranty for details.



# FIREHAWK™ GT V

ALL-SEASON PERFORMANCE



**SPECIALLY BUILT TO  
GIVE YOU CONFIDENT  
HANDLING AND  
ALL-SEASON GRIP**

## FEATURES AND BENEFITS



Precise handling and steering response



Confident wet performance



All-season performance




Engineered specifically to complement  
your vehicle as Original Equipment

**50,000**

MILE LIMITED WARRANTY\*

**80,000**

KILOMETRE LIMITED WARRANTY†



### Tread Pattern

tuned for wet and dry handling

### Circumferential Grooves

channel water away from the  
tire's contact area

### Tread Compound

formulated for all-season grip

\* Conditions apply. See FirestoneTire.com/Warranty for details.

**Firestone**



# FIREHAWK™ GT V

## Top Fitments

- Chrysler 300
- Dodge Challenger
- Dodge Charger

## Warranty\*

- 50,000 Mile Limited Warranty
- Gold Pledge Limited Warranty
- 90-Day Buy & Try™ Guarantee



## Tire Specifications Legend

Δ	B-Silent	BW	Blackwall	~	Pinned for #12 Stud Sizes
*	OEM Tire	OWL	Outline White Letter	f	Pinned for #15 Stud Sizes
‡	MOE (Mercedes Exclusive)	XL	Extra Load (XL)	**	Pinned for #16 Stud Sizes
^	RFT (Run Flat Tire)	◆	Pinned for #11 Stud Sizes	***	Pinned for #17 Stud Sizes

## Tire Specifications

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd Mile)	Revs Per Mile	UTQG	WT
20" Rim Diameter											
245/45R20 99V *		134054	BW	7.5-9.0	8.0	28.7	9.6	11	724	460 A.A.	30

# FIREHAWK™ PURSUIT™

PURSUIT, ULTRA-HIGH PERFORMANCE - ALL-SEASON



## SOME TIRES LEAD AND PURSUE AT THE SAME TIME

### Features & Benefits




Designed for law enforcement and high speed emergency use



All-season performance with improved wet handling<sup>1</sup>



Improved fuel efficiency reduces operating costs to keep your fleet moving<sup>2</sup>



**Pursuit-Specific Construction**  
for high speed stability, handling performance, and durability

**New Tread Pattern with Full-Depth 3D Sipes**  
for improved wet and snow performance while maintaining stiffness for handling performance and stability<sup>1</sup>

**Increased See-Through Void**  
and more balanced rib/groove distribution<sup>1</sup>

1 Comparison based on Firestone Firehawk Pursuit vs. the Goodyear Eagle RSA tire and Goodyear Enforcer tire from internal testing. Results based on driving on dry, wet, and snow conditions. 2 Comparison based on Firestone Firehawk Pursuit vs. the Firehawk GT Pursuit tire, the Cooper Eagle RSA tire and the General G-MAX™ Justice tire from internal testing. Results may vary depending on proper tire and vehicle maintenance, road conditions, and driving habits.

# Firestone





# FIREHAWK™ PURSUIT™

## Top Fitments

- Dodge Charger Pursuit
- Chevrolet Caprice
- Ford Interceptor

## Tire Specifications Legend

Δ	B-Silent	BW	Blackwall	~	Pinned for #12 Stud Sizes
*	OEM Tire	OWL	Outline White Letter	f	Pinned for #15 Stud Sizes
‡	MOE (Mercedes Exclusive)	XL	Extra Load (XL)	**	Pinned for #16 Stud Sizes
^	RFT (Run Flat Tire)	◆	Pinned for #11 Stud Sizes	***	Pinned for #17 Stud Sizes

## Tire Specifications

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd)	Revs Per Mile	UTOG	WT
<b>17" Rim Diameter</b>											
265/60R17 108V		011685	BW	7.5-9.5	8.0	29.5	10.7	9	706	640 AAA	35
235/55R17 99W		011687	BW	6.5-8.5	7.5	27.2	9.7	9	767	640 AAA	28
235/50R17 96W		011494	BW	6.5-8.5	7.5	26.3	9.7	9	792	640 AAA	27
<b>18" Rim Diameter</b>											
225/60R18 100W		011688	BW	6.0-8.0	6.5	28.6	9.0	9	728	640 AAA	29
255/60R18 108V*		012114	BW	7.0-9.0	7.5	30.0	10.2	9	683	640 AAA	35
245/55R18 103W		000702	BW	7.0-8.5	7.5	28.6	10.0	9	728	640 AAA	31
235/50R18 101W		XL 011686	BW	6.5-8.5	7.5	27.3	9.7	9	764	640 AAA	29
<b>20" Rim Diameter</b>											
275/65R20 113V*		008921	BW	7.5-9.5	8.5	31.9	11.2	9	653	640 AAA	40
265/60R20 107V		013789	BW	7.5-9.5	8.5	30.5	10.9	9	684	640 AAA	37

# FIREHAWK™ PURSUIT™ AWT

PURSUIT, ALL-WEATHER



## PURSUIT IN ANY FORECAST

### Features & Benefits




Designed with 3-Peak Mountain Snowflake Certification for high speed emergency use in winter conditions



High speed handling with solid traction in wet and snow



Thousands of biting edges help provide traction in the wet and snow



**Pursuit-Specific Construction** for high speed stability, handling performance, and durability

**New Tread Pattern and Compound** provide all-weather capability with certified 3-Peak Mountain Snowflake snow traction performance for confident control in winter conditions

**New Tread Pattern with Full-Depth 3D Sipes** for improved wet and snow performance while maintaining stiffness for handling performance and stability<sup>1</sup>

<sup>1</sup> Comparison based on the Firestone Firehawk Pursuit AWT tire vs. the Firehawk PWS tire from internal testing. Results may vary depending on proper tire and vehicle maintenance, road conditions, and driving habits.

# Firestone

# FIREHAWK™ PURSUIT AWT



## Top Fitments

- Dodge Charger Pursuit
- Chevrolet Tahoe
- Ford Interceptor

## Tire Specifications Legend

Δ	B-Silent	BW	Blackwall	~	Pinned for #12 Stud Sizes
*	OEM Tire	OWL	Outline White Letter	f	Pinned for #15 Stud Sizes
‡	MOE (Mercedes Exclusive)	XL	Extra Load (XL)	**	Pinned for #16 Stud Sizes
^	RFT (Run Flat Tire)	◆	Pinned for #11 Stud Sizes	***	Pinned for #17 Stud Sizes

## Tire Specifications

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd)	Revs Per Mile	UTOG	Wt
<b>17" Rim Diameter</b>											
265/60R17 108V		011691	BW	7.5-9.5	8.0	29.5	10.7	10	706	600 A.A.	34
235/50R17 96V		011496	BW	6.5-8.5	7.5	26.3	9.7	10	792	600 A.A.	27
<b>18" Rim Diameter</b>											
225/60R18 100V		011690	BW	6.0-8.0	6.5	26.6	9.0	10	728	600 A.A.	29
255/60R18 108V		011894	BW	7.0-9.0	7.5	30.0	10.2	10	693	600 A.A.	34
245/55R18 103V		000694	BW	7.0-8.5	7.5	28.6	10.0	10	728	600 A.A.	31
<b>20" Rim Diameter</b>											
275/55R20 113V		011822	BW	7.5-9.5	8.5	31.9	11.2	10	653	600 A.A.	41

# DESTINATION™ LE3

CUV, SUV & TRUCK - HIGHWAY



## IT'S OUR BEST-SELLING TIRE FOR A REASON

### Features & Benefits


Firestone's longest limited warranty<sup>†</sup>

Sustained performance throughout tread life

Dependable wet, dry and snow performance

**70,000**  
MILE LIMITED WARRANTY\*

**110,000**  
KILOMETRE LIMITED WARRANTY\*



#### TractionTech™ Technology

A full-depth tread design that is engineered to maintain performance throughout the tire's supplemental mileage limited warranty period<sup>†</sup>

#### Hydro-Grip™ Technology

for enhanced water evacuation from contact patch under wet conditions<sup>†</sup>

#### Full-Depth 3D Sipes

for enhanced snow traction and improved performance throughout the tire's limited warranty<sup>†</sup>

<sup>†</sup> Conditions apply. See FirestoneTire.com/warranty for details.  
<sup>1</sup> Comparison based on Firestone Destination LE3 vs. Firestone Destination LE2 from internal testing. Results may vary depending on proper tire and vehicle maintenance, road conditions, and driving habits.

# Firestone



# DESTINATION™ LE3

## Top Fitsments

- Chevrolet Silverado
- Ford F-150
- Dodge RAM 1500
- RAV4
- Honda CRV

## Warranty\*

- 70,000 Mile Limited Warranty
- Gold Pledge Limited Warranty
- 90-Day Buy & Try™ Guarantee



## Tire Specifications

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd Mile)	Revs Per Mile	UTQG	Wt
-----------------------------------	------------	-------------	------------------	---------------------	----------------------	-----------------------	-----------------------	-------------------------	---------------	------	----

15" Rim Diameter											
215/75R15 100T		005343	OWL	5.5-7.0	6.0	27.7	8.5	10	753	700 A B	25
225/75R15 102T		005344	OWL	6.0-7.5	6.0	28.3	8.8	10	736	700 A B	26
235/75R15 109T	XL	014819	BW	-	-	-	-	10	-	700 A B	28
265/75R15 112T		005348	OWL	7.0-9.0	7.5	30.7	10.5	10	679	700 A B	34
225/70R15 100T		005345	OWL	6.0-7.5	6.5	27.4	9.0	10	759	700 A B	24

16" Rim Diameter											
225/75R16 104T		005334	OWL	6.0-7.5	6.0	29.3	8.8	10	711	700 A B	26
235/75R16 108T		005336	OWL	6.0-8.0	7.0	29.8	9.3	10	698	700 A B	29
245/75R16 111T		005340	OWL	6.5-8.0	7.0	30.5	9.8	10	684	700 A B	31
265/75R16 116T		005353	OWL	7.0-9.0	8.0	31.7	10.5	10	658	700 A B	35
295/70R16 97H		005349	BW	5.0-7.0	6.0	27.3	8.2	10	762	700 A B	22
215/70R16 100H		005350	BW	5.5-7.0	6.5	27.9	8.7	10	747	700 A B	23
225/70R16 103T		005335	OWL	6.0-7.5	6.5	28.4	9.0	10	733	700 A B	24
235/70R16 106T		014817	BW	-	-	-	-	10	-	700 A B	28
245/70R16 107T		005341	OWL	6.5-8.0	7.0	29.5	9.8	10	705	700 A B	30
265/70R16 111T		005342	OWL	6.5-8.5	8.0	30.1	10.2	10	693	700 A B	33
285/70R16 112T		005354	OWL	7.0-9.0	8.0	30.6	10.7	10	680	700 A B	35
215/65R16 98H		005351	BW	6.0-7.5	6.5	27.0	8.7	10	771	700 A B	23
235/65R16 103H		005339	BW	6.5-8.5	7.0	28.0	9.5	10	743	700 A B	25
255/65R16 109T		005332	OWL	7.0-9.0	7.5	29.1	10.2	10	717	700 A B	31

17" Rim Diameter											
235/70R17 109T	XL	005362	OWL	6.0-8.0	7.0	30.0	9.5	10	719	700 A B	31
245/70R17 110T		005369	OWL	6.5-8.0	8.0	30.6	9.8	10	682	700 A B	32
265/70R17 112T		005371	OWL	6.5-8.5	8.0	31.1	10.2	10	670	700 A B	34
285/70R17 115T		005374	OWL	7.0-9.0	8.0	31.7	10.7	12	658	700 A B	36
215/65R17 99H		005357	BW	6.0-7.5	6.5	28.0	8.7	10	743	700 A B	26
225/65R17 102H		005359	BW	6.0-8.0	6.5	28.5	9.0	10	731	700 A B	24
235/65R17 104H		005365	BW	6.5-8.5	7.0	29.1	9.5	10	717	700 A B	25
245/65R17 107T		014818	BW	-	-	-	-	10	-	700 A B	29
265/65R17 110T		005372	OWL	7.0-9.0	8.0	30.1	10.2	10	693	700 A B	33
285/65R17 112T		005375	OWL	7.5-9.5	8.0	30.6	10.7	10	682	700 A B	34
215/60R17 96H		005338	BW	6.0-7.5	6.5	27.2	8.7	10	767	700 A B	24
225/60R17 98H		005390	BW	6.0-8.0	6.5	27.6	9.0	10	754	700 A B	23
235/60R17 102H		005366	BW	6.5-8.5	7.0	28.1	9.5	10	741	700 A B	24
255/60R17 107H		005361	BW	6.0-8.0	7.0	28.8	9.2	10	778	700 A B	23
235/65R17 99H		005368	BW	6.5-8.5	7.5	27.2	8.7	10	767	700 A B	24

Firestone Tire.com | © 2024 Bridgestone Americas Tire Operations, LLC.

Rev: 1/2024 EN



## Tire Specifications Legend

- △ B-Silent
- \* OEM Tire
- ¥ MOE (Mercedes Exclusive)
- ^ RFT (Run Flat Tire)
- BW Blackwall
- OWL Outline White Letter
- XL Extra Load (XL)
- ◆ Pinned for #11 Stud Sizes
- ~ Pinned for #12 Stud Sizes
- f Pinned for #15 Stud Sizes
- \*\* Pinned for #16 Stud Sizes
- \*\*\* Pinned for #17 Stud Sizes

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd Mile)	Revs Per Mile	UTQG	Wt
-----------------------------------	------------	-------------	------------------	---------------------	----------------------	-----------------------	-----------------------	-------------------------	---------------	------	----

18" Rim Diameter											
255/70R18 113T		005385	OWL	6.5-8.5	7.5	32.1	10.2	10	649	700 A B	35
265/70R18 116T		005388	OWL	7.0-8.0	8.0	32.6	10.7	10	638	700 A B	37
235/65R18 106T		014838	BW	6.5-8.5	7.0	30.0	9.5	10	693	700 A B	29
255/65R18 111H		005386	BW	7.0-9.0	7.5	31.1	10.2	10	671	700 A B	35
265/65R18 114T		014839	BW	7.5-9.5	8.0	31.5	10.7	10	660	700 A B	37
275/65R18 116T		005392	OWL	7.5-8.5	8.0	32.1	11.4	10	649	700 A B	38
225/60R18 100H		005376	BW	6.0-8.0	6.5	28.6	9.0	10	728	700 A B	25
235/60R18 103H		005380	BW	6.5-8.5	7.0	29.1	9.5	10	716	700 A B	26
245/60R18 105H		005384	BW	7.0-8.5	7.0	29.6	9.8	10	704	700 A B	29
265/60R18 110T		014837	BW	7.5-8.5	8.0	30.5	10.2	10	683	700 A B	34
225/55R18 98H		005378	BW	6.0-8.0	7.0	27.8	9.2	10	749	700 A B	23
235/55R18 100V		005382	BW	6.5-8.5	7.5	28.2	9.7	10	740	700 A B	33
255/55R18 108H	XL	005387	BW	7.0-8.0	8.0	29.0	10.4	10	718	700 A B	32
235/50R18 97H		005383	BW	6.5-8.5	7.5	27.3	9.7	10	764	700 A B	25

19" Rim Diameter											
255/60R19 108H		005403	BW	7.0-9.0	7.5	31.1	10.2	10	671	700 A B	35
225/55R19 98H		005393	BW	6.0-8.0	7.0	28.8	9.2	10	724	700 A B	25
235/55R19 101H		005394	BW	6.5-8.5	7.5	29.2	9.7	10	714	700 A B	27
245/55R19 103H		005397	BW	7.0-8.5	7.5	29.7	10.0	10	703	700 A B	35
275/55R19 111H		005399	BW	7.5-9.5	8.5	30.9	11.2	10	674	700 A B	40
235/50R19 98H		005385	BW	6.5-8.5	7.5	28.3	9.7	10	736	700 A B	24
255/50R19 107H	XL	005398	BW	7.0-9.0	8.0	29.1	10.4	10	716	700 A B	32
235/45R19 96H		005396	BW	7.5-9.0	8.0	27.4	9.3	10	761	700 A B	26

20" Rim Diameter											
245/60R20 107H		005412	BW	7.0-8.5	7.0	31.6	9.8	10	660	700 A B	35
275/60R20 115H		005409	BW	7.5-8.5	8.0	33.0	11.0	10	631	700 A B	39
235/55R20 102H		005400	BW	6.5-8.5	7.5	30.2	9.7	10	691	700 A B	28
255/55R20 107H		005405	BW	7.0-9.0	8.0	31.0	10.4	10	672	700 A B	37
275/55R20 113H		005410	BW	7.5-8.5	8.5	31.9	11.2	10	653	700 A B	38
245/50R20 102H		005401	BW	7.0-8.5	7.5	29.7	10.0	10	702	700 A B	30
255/50R20 109H	XL	005406	BW	7.0-9.0	8.0	30.1	10.4	10	693	700 A B	33
265/50R20 110H		005408	BW	7.5-9.5	8.5	30.5	10.9	10	684	700 A B	35
275/45R20 110H	XL	005411	BW	8.5-10.5	9.0	28.8	10.8	10	700	700 A B	35
285/45R22 110H		005413	BW	9.0-10.5	9.5	32.1	11.2	10	649	700 A B	38

† Conditions apply. See FirestoneTire.com/warranty for details.

# DESTINATION™ LE2

TRUCK & SUV - HIGHWAY



## BUILT TO KEEP UP WITH YOU

### FEATURES AND BENEFITS



All-season performance



60,000 mile limited warranty\*



Built to last with solid wet and dry performance


UP TO

**60,000**

MILE LIMITED WARRANTY

**100,000**

KILOMETRE LIMITED WARRANTY\*



**Continuous Closed Shoulder Blocks** help with dry performance and treadwear

**Wide Circumferential Grooves** channel water away from the tread to assist with wet performance

**Long-Lasting Tread Compound** offers a 60,000 mile limited warranty\*

\* Conditions apply. See FirestoneTire.com/Warranty for details.

**Firestone**



# DESTINATION™ LE2

## Top Fitments

- Chevrolet Silverado
- Jeep Grand Cherokee
- Honda Element
- Nissan Murano

## Warranty\*

- 60,000 Mile Limited Warranty
- Gold Pledge Limited Warranty
- 90-Day Buy & Try™ Guarantee



## Tire Specifications Legend

△	B-Silent	BW	Blackwall	~	Pinned for #12 Stud Sizes
*	OEM Tire	OWL	Outline White Letter	f	Pinned for #15 Stud Sizes
¥	MOE (Mercedes Exclusive)	XL	Extra Load (XL)	**	Pinned for #16 Stud Sizes
^	RFT (Run Flat Tire)	◆	Pinned for #11 Stud Sizes	***	Pinned for #17 Stud Sizes

## Tire Specifications

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd)	Revs Per Mile	UTOG	WT
<b>16" Rim Diameter</b>											
P245/75R16 109S *		000223	BW	6.5-8.0	7.0	30.5	9.8	11	684	520 A.B	32
<b>17" Rim Diameter</b>											
225/65R17 102T *		003352	BW	6.0-8.0	6.5	28.5	9.0	10	731	520 A.B	24
225/65R17 102H *		006578	BW	6.0-8.0	6.5	28.5	9.0	10	731	520 A.B	25
P265/65R17 110S *		006513	BW	7.5-9.5	8.0	30.6	10.7	11	682	520 A.B	34
225/60R17 99T *		003351	BW	6.0-8.0	6.5	27.6	9.0	10	754	520 A.B	24
225/60R17 99T *		006777	BW	6.0-8.0	6.5	27.6	9.0	10	754	520 A.B	25
<b>18" Rim Diameter</b>											
245/60R18 105H *		002360	BW	7.0-8.5	7.0	29.6	9.8	11	704	520 A.A	32
245/60R18 105H *		011785	BW	7.0-8.5	7.0	29.6	9.8	10	704	520 A.B	31



# DESTINATION™ A/T2

ALL-WEATHER, ALL-TERRAIN TRUCK & SUV



## BUILT TOUGH FOR DEPENDABILITY, ON OR OFF-ROAD

### Features & Benefits



Dependable on and off-road traction



Longer-lasting performance<sup>1</sup>



Built for wet performance and on-road handling, plus 3-Peak Mountain Snowflake certification


UP TO

**55,000**

MILE LIMITED WARRANTY

**90,000**

KILOMETRE LIMITED WARRANTY



#### **Aggressive Shoulder Tread Pattern**

helps to improve off-road handling

#### **Full-Depth Interlocking 3D Sipe Technology**

helps to provide even wear and consistent performance through the limited mileage warranty period

#### **Increased Surface and See-Through Void**

helps to improve water evacuation to improve wet stopping and handling

† Conditions apply. See FirestoneTire.com/warranty for details.  
1 Comparison based on the Firestone Destination A/T2 tire vs. the Firestone Destination A/T tire from internal testing. Results may vary depending on proper tire and vehicle maintenance, road conditions, and driving habits.

# Firestone





# DESTINATION™ A/T2

## Top Fitsments

- Ford F-150
- Chevrolet Silverado
- Toyota 4Runner TRD Pro
- Chevrolet Tahoe
- Jeep Grand Cherokee

## Warranty\*

- 55,000 Mile Limited Warranty (Excludes certain sizes)
- Gold Pledge Limited Warranty
- 90-Day Buy & Try™ Guarantee



## Tire Specifications

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd)	Revs Per Mile	UTQG	Wt
<b>15" Rim Diameter</b>											
P235/75R15 105S		014043	OWL	6.0-8.0	6.5	28.9	9.3	12	722	540 A B	30
<b>16" Rim Diameter</b>											
P225/75R16 104S		014111	OWL	6.0-7.5	6.0	29.3	8.8	12	711	540 A B	34
P235/75R16 106S		005284	OWL	6.0-8.0	6.5	29.8	9.3	12	688	540 A B	31
P245/75R16 108S		014145	OWL	6.5-8.0	7.0	30.5	9.8	12	684	540 A B	34
P265/55R16 114T		014162	OWL	7.0-9.0	7.5	31.7	10.5	12	658	540 A B	38
P235/70R16 104S		014213	OWL	6.0-8.0	7.0	29.0	9.5	12	719	540 A B	30
P245/70R16 106S		014247	OWL	6.5-8.0	7.0	29.5	9.8	12	705	540 A B	33
P255/70R16 109S		014284	OWL	6.5-8.5	7.5	30.1	10.2	12	693	540 A B	36
P265/70R16 111T		014288	OWL	7.0-9.0	8.0	30.6	10.7	12	680	540 A B	35
<b>17" Rim Diameter</b>											
P235/75R17 108S		014315	OWL	6.0-8.0	6.5	30.9	9.3	12	675	540 A B	34
245/75R17 112S		013915	BW	6.5-8.0	7.0	31.5	9.8	12	661	540 A B	35
P255/75R17 113S		014349	OWL	6.5-8.5	7.0	32.1	10.0	12	650	540 A B	37
P235/70R17 108S		XL 014366	OWL	6.0-8.0	7.0	30.0	9.5	12	694	540 A B	32
P245/70R17 109S		014383	OWL	6.5-8.0	7.0	30.6	9.8	12	682	540 A B	35
P255/70R17 110S		014417	OWL	6.5-8.5	7.5	31.1	10.2	12	670	540 A B	36
P265/70R17 113S		014434	OWL	7.0-9.0	8.0	31.7	10.7	12	658	540 A B	38
P285/70R17 117T		014468	OWL	7.5-9.5	8.5	32.8	11.5	12	636	540 A B	42
225/65R17 102H		013911	BW	6.0-8.0	6.5	28.5	9.0	12	731	540 A B	26
P235/65R17 109S		014502	OWL	6.5-8.5	7.0	29.1	9.5	12	717	540 A B	29
P245/65R17 105T		014519	OWL	7.0-8.5	7.0	29.5	9.8	12	705	540 A B	33
P265/65R17 110S		014553	OWL	7.5-9.5	8.0	30.6	10.7	12	682	540 A B	36
225/60R17 99H		013912	BW	6.0-8.0	6.5	27.6	9.0	12	754	540 A B	25

## Tire Specifications Legend

△ B-Silent	BW Blackwall	~ Pinned for #12 Stud Sizes
* OEM Tire	OWL Outline White Letter	f Pinned for #15 Stud Sizes
¥ MOE (Mercedes Exclusive)	XL Extra Load (XL)	** Pinned for #16 Stud Sizes
^ RFT (Run Flat Tire)	◆ Pinned for #11 Stud Sizes	*** Pinned for #17 Stud Sizes

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd)	Revs Per Mile	UTQG	Wt
<b>18" Rim Diameter</b>											
P255/70R18 112S		014570	OWL	6.5-8.5	7.5	32.1	10.2	12	649	540 A B	38
P285/70R18 114S		014587	OWL	7.0-9.0	8.0	32.6	10.7	12	638	540 A B	40
P265/65R18 112S		014689	OWL	7.5-9.5	8.0	31.5	10.7	12	660	540 A B	39
275/65R18 116T*		012112	BW	7.5-9.5	8.0	32.1	11.4	12	649	540 A B	39
P275/65R18 114T		014706	OWL	7.5-9.5	8.0	32.1	11.0	12	649	540 A B	41
225/60R18 100H		013913	BW	6.0-8.0	6.5	28.6	9.0	12	728	560 A B	26
P245/60R18 104T		014723	BW	7.0-8.5	7.0	29.6	9.8	12	704	540 A B	32
P265/60R18 109T		014740	OWL	7.0-9.5	8.0	30.5	10.7	12	683	540 A B	38
<b>20" Rim Diameter</b>											
245/60R20 107H		013914	BW	7.0-8.5	7.0	31.6	9.8	10	660	540 A B	35
P275/60R20 114S		014757	OWL	7.5-9.5	8.0	33.0	11.0	12	631	540 A B	43
P275/55R20 111S		014774	BW	7.5-9.5	8.5	31.9	11.2	12	653	540 A B	44
<b>22" Rim Diameter</b>											
285/45R22 114H	XL	005214	BW	9.0-10.5	9.5	32.1	11.2	12	649	540 A B	41

\* Conditions apply. See FirestoneTire.com/warranty for details.

Rev: 1/2024 EN

Firestone Tire.com | © 2024 Bridgestone Americas Tire Operations, LLC.



# DESTINATION™ X/T

ALL-WEATHER, ALL-TERRAIN LIGHT TRUCK & SUV



## NEVER BACK DOWN FROM CHALLENGING TERRAIN

### Features & Benefits



Masters muddy terrain to help prevent slipping, spinning or getting stuck



Delivers confident off-road traction in wet conditions



3-Peak Mountain Snowflake Certified




On-Road Wet Performance

50,000

MILE LIMITED WARRANTY\*

80,000

KILOMETRE LIMITED WARRANTY\*



**Staggered Shoulder Lugs**  
and an aggressive off-shoulder tread design provide extra biting edges for off-road performance

**Full-Depth Interlocking 3D Sipe Technology**  
helps to provide even wear and consistent performance through the limited mileage warranty period

**Open Shoulder Slots**  
provide off-road traction and also evacuate water to help reduce the risk of hydroplaning

# Firestone

\* Conditions apply. See FirestoneTire.com/Warranty for details.



# DESTINATION™ X/T

## Top Fitsments

- Chevrolet Silverado
- Ford F-250
- Ford F-350
- GMC Sierra
- Jeep Wrangler Rubicon

## Warranty\*

- 50,000 Mile Limited Warranty
- Gold Pledge Limited Warranty
- 90-Day Buy & Try™ Guarantee



## Tire Specifications

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32/32)	Minimum Dual Spacing	Revs Per Mile	UTQG	Wt.
-----------------------------------	------------	-------------	------------------	---------------------	----------------------	-----------------------	-----------------------	---------------------	----------------------	---------------	------	-----

16" Rim Diameter - LT METRIC												
LT215/65R16 115/125S	E	004388	BW	5.5-7.0	6.0	30.4	8.5	14	9.9	685	-	37
LT235/65R16 120/116S	E	004381	BW	6.0-7.5	6.5	31.7	9.3	14	10.8	658	-	40
LT225/75R16 115/112S	E	004379	BW	6.0-7.0	6.0	29.3	8.8	14	10.2	711	-	35
LT245/75R16 120/116S	E	004374	BW	6.5-8.0	7.0	30.5	9.8	14	11.3	684	-	39
LT285/75R16 120/120S	E	004376	OWL	7.0-8.0	7.5	31.7	10.5	15	12.2	658	-	45
LT285/75R16 126/123R	E	009608	OWL	7.5-9.0	8.0	32.8	11.3	16	13.1	634	-	52

17" Rim Diameter - LT METRIC												
LT235/65R17 120/117S	E	004384	BW	6.0-7.5	6.5	31.8	9.3	14	10.8	655	-	40
LT245/75R17 121/118S	E	004375	OWL	6.5-7.5	7.0	31.5	9.8	14	11.3	661	-	42
LT255/75R17 119/108T	C	004393	BW	6.5-8.5	7.0	32.1	10.0	15	11.7	650	-	41
LT285/75R17 121/116S	D	013022	BW	7.5-9.5	8.0	33.9	11.3	16	-	615	-	54
LT245/75R17 119/116S	E	004385	OWL	6.5-8.0	7.0	30.6	9.8	14	11.3	682	-	42
LT265/70R17 121/118S	E	004373	OWL	7.0-8.5	8.0	31.7	10.7	15	12.4	658	-	46
LT275/70R17 121/118R	E	008381	OWL	7.0-8.5	8.0	32.2	11.0	16	12.8	647	-	49
LT285/70R17 121/118S	E	004383	BW	7.5-9.0	8.5	32.8	11.5	16	13.4	636	-	50
LT305/70R17 121/118R	E	013818	BW	-	9.0	33.8	12.2	16	-	616	-	58
LT315/70R17 121/118R	E	006135	OWL	8.5-10.0	9.5	34.4	12.7	17	14.8	605	-	61
LT285/65R17 120/117S	E	013026	BW	-	8.0	30.6	10.7	12	-	682	-	44

18" Rim Diameter - LT METRIC												
LT235/65R18 124/121S	E	004386	BW	7.0-9.0	8.0	32.6	10.7	15	12.4	638	-	47
LT255/70R18 125/122S	E	004377	OWL	7.0-8.5	8.0	33.2	11.0	16	12.8	628	-	50
LT285/65R18 122/119S	E	015058	BW	-	8.0	31.6	31.6	12	-	657	-	46
LT275/65R18 123/120S	E	004380	OWL	7.5-9.0	8.0	32.1	11.0	16	12.8	649	-	49
LT285/65R18 126/122R	E	008375	BW	8.0-10.0	8.5	32.6	11.5	16	13.4	640	-	50

20" Rim Diameter - LT METRIC												
LT275/65R20 126/123S	E	004382	OWL	7.5-9.5	8.0	34.1	11.0	16	12.8	611	-	53
LT285/65R20 127/124S	E	008386	BW	8.0-10.0	8.5	34.6	11.5	16	13.4	603	-	53
LT265/60R20 121/116S	E	004392	BW	7.5-9.5	8.0	32.5	10.7	15	12.4	641	-	48
LT275/60R20 123/120R	E	008383	BW	7.5-9.5	8.0	33.0	11.0	16	12.8	631	-	52
LT285/60R20 126/122S	E	004390	BW	8.0-10.0	8.5	33.5	11.5	16	13.4	623	-	53
LT295/60R20 126/123S	E	008388	BW	8.0-10.0	8.5	33.9	11.8	16	13.7	614	-	57
LT275/65R20 120/117R	E	008380	BW	7.5-9.5	8.5	31.9	11.2	16	13.0	653	-	49
LT285/65R20 122/119R	E	008376	BW	8.0-10.0	9.0	32.4	11.7	16	13.6	644	-	53
LT305/65R20 121/118R	E	008377	BW	8.5-11.0	9.5	33.2	12.4	16	14.5	627	-	57

## Tire Specifications Legend

△ B-Silent	BW Blackwall	~ Pinned for #12 Stud Sizes
* OEM Tire	OWL Outline White Letter	f Pinned for #15 Stud Sizes
‡ MOE (Mercedes Exclusive)	XL Extra Load (XL)	** Pinned for #16 Stud Sizes
^ RFT (Run Flat Tire)	◆ Pinned for #11 Stud Sizes	*** Pinned for #17 Stud Sizes

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32/32)	Minimum Dual Spacing	Revs Per Mile	UTQG	Wt.
-----------------------------------	------------	-------------	------------------	---------------------	----------------------	-----------------------	-----------------------	---------------------	----------------------	---------------	------	-----

15" Rim Diameter - FLOTATION												
30X9.50R15LT 104R	C	006133	OWL	6.5-8.5	7.5	29.5	9.5	14	-	706	-	36
31X10.50R15LT 109R	C	004389	OWL	7.0-9.0	8.5	30.5	10.5	15	-	683	-	41
33X12.50R15LT 108R	C	006134	OWL	8.5-11.0	10.0	32.5	12.5	17	-	641	-	51

18" Rim Diameter - FLOTATION												
33X12.50R18LT 116S	E	013916	BW	8.5-11.0	10.0	32.5	12.5	17	-	641	-	55
35X12.50R18LT 123R	E	006412	OWL	8.5-11.0	10.0	34.5	12.5	17	-	603	-	60

20" Rim Diameter - FLOTATION												
35X12.50R20LT 121R	E	006132	OWL	8.5-11.0	10.0	34.5	12.5	17	-	603	-	60

\* Conditions apply. See FirestoneTire.com/warranty for details.

Rev: 1/2024 EN

Firestone Tire.com | © 2024 Bridgestone Americas Tire Operations, LLC.



# DESTINATION™ M/T2

TRUCK & SUV - MAXIMUM TRACTION



## TOUGH ENOUGH TO GO WHEREVER THE TRAIL TAKES YOU

### Features & Benefits



Traction for tough trails




Confident control in mud



Debris shield for added durability



Impressive performance in wet and snowy conditions



#### Mud and Stone Rejector Technology

clears debris from the tread to deliver superior mud traction performance compared to the General Grabber™ X3 tires<sup>1</sup>

#### 20% More Biting Edges and Pinned for Studs

provide rugged off-road traction in wet, mud and snowy conditions<sup>2</sup> with optional studs for added ice traction

#### New Tread Compound, 3-Ply Sidewall Construction, and More Aggressive Upper Sidewall Lugs

deliver added durability and stronger resistance to chips and tears<sup>2</sup>

#### Debris Shield

prevents trail debris from wedging between the tire and the wheel, potentially causing damage and pressure loss

1 Comparison based on the Firestone Destination M/T2 tires vs. the General Grabber™ X3 tires from internal testing. Results may vary depending on proper tire and vehicle maintenance, road conditions, and driving habits.  
2 Comparison based on the Firestone Destination M/T2 tire vs. the Destination M/T tire from internal testing. Results may vary depending on proper tire and vehicle maintenance, road conditions, and driving habits.

# Firestone



# DESTINATION™ M/T2

## Top Fitsments

- Toyota Tacoma TRD
- Jeep Wrangler
- Jeep Rubicon

## Warranty\*

- Gold Pledge Limited Warranty
- 90-Day Buy & Try™ Guarantee



## Tire Specifications

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd)	Minimum Spacing	Revs Per Mile	UTQG	Wt.
-----------------------------------	------------	-------------	------------------	---------------------	----------------------	-----------------------	-----------------------	--------------------	-----------------	---------------	------	-----

15" Rim Diameter - LT METRIC												
LT235/75R15 104/101Q **	C	003493	OWL	6.0-7.0	6.5	28.9	9.3	19	10.8	722	-	40

16" Rim Diameter - LT METRIC												
LT235/65R16 120/116Q **	E	003462	BW	6.0-7.5	6.5	31.7	9.3	19	10.8	656	-	49
LT245/75R16 120/116Q **	E	245587	BW	6.5-8.0	7.0	30.5	9.8	19	11.3	684	-	48
LT265/75R16 123/120Q **	E	245604	OWL	7.0-8.0	7.5	31.7	10.5	19	12.2	658	-	53
LT285/75R16 126/123Q **	E	245621	OWL	7.5-9.0	8.0	32.8	11.3	20	13.1	634	-	60
LT315/75R16 127/124Q ***	E	003461	BW	8.0-10.0	8.5	34.6	12.3	21	14.3	603	-	66

17" Rim Diameter - LT METRIC												
LT245/75R17 121/118Q **	E	003459	OWL	6.5-7.5	7.0	31.5	9.8	19	11.3	661	-	50
LT255/75R17 111/109Q ***	C	011618	OWL	6.5-8.5	7.0	32.1	10.0	19	11.7	650	-	50
LT265/75R17 121/118Q **	E	245723	OWL	7.0-8.5	8.0	31.7	10.7	19	12.4	668	-	53
LT285/75R17 121/118Q **	E	245740	BW	7.5-9.0	8.5	32.8	11.5	20	13.4	636	-	60
LT295/75R17 121/118Q **	E	003608	BW	7.5-10.0	8.5	33.5	11.8	21	13.7	625	-	66
LT315/75R17 121/118Q **	E	245757	BW	8.5-10.0	9.5	34.4	12.7	21	14.8	605	-	67

18" Rim Diameter - LT METRIC												
LT275/70R18 125/122Q **	E	245825	OWL	7.0-8.5	8.0	33.2	11.0	20	12.8	628	-	60
LT285/70R18 129/126Q **	E	003456	BW	7.5-10.0	8.5	34.3	11.8	21	13.7	607	-	66
LT295/65R18 123/120Q **	E	003457	BW	7.5-9.0	8.0	32.1	11.0	20	12.8	649	-	55
LT285/65R18 125/122Q **	E	245659	BW	8.0-10.0	8.5	32.6	11.5	20	13.4	640	-	58

20" Rim Diameter - LT METRIC												
LT275/65R20 126/123Q **	E	245927	BW	7.5-9.5	8.0	34.3	11.0	20	12.8	611	-	58

## Tire Specifications Legend

△ B-Silent	BW Blackwall	~ Pinned for #12 Stud Sizes
* OEM Tire	OWL Outline White Letter	f Pinned for #15 Stud Sizes
¥ MOE (Mercedes Exclusive)	XL Extra Load (XL)	** Pinned for #16 Stud Sizes
^ RFT (Run Flat Tire)	◆ Pinned for #11 Stud Sizes	*** Pinned for #17 Stud Sizes

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd)	Minimum Spacing	Revs Per Mile	UTQG	Wt.
-----------------------------------	------------	-------------	------------------	---------------------	----------------------	-----------------------	-----------------------	--------------------	-----------------	---------------	------	-----

15" Rim Diameter - FLOTATION												
31X10.50R15LT 109Q **	C	245502	OWL	7.0-9.0	8.5	30.5	10.5	20	-	683	-	47
33X12.50R15LT 109Q ***	C	245519	OWL	8.5-11.0	10.0	32.5	12.5	22	-	641	-	58

17" Rim Diameter - FLOTATION												
35X12.50R17LT 120Q **	E	003815	BW	8.5-11.0	10.0	32.8	12.5	21	-	641	-	67
35X12.50R17LT 121Q ***	E	003810	BW	8.5-11.0	10.0	34.8	12.5	21	-	603	-	73
37X12.50R17LT 124Q ***	D	003803	BW	8.5-11.0	10.0	36.8	12.5	21	-	570	-	81

18" Rim Diameter - FLOTATION												
35X12.50R18LT 123Q **	E	003811	BW	8.5-11.0	10.0	34.8	12.5	21	-	603	-	73

20" Rim Diameter - FLOTATION												
33X12.50R20LT 114Q ***	E	003813	BW	8.5-11.0	10.0	32.8	12.5	21	-	641	-	68
35X12.50R20LT 121Q **	E	003812	BW	8.5-11.0	10.0	34.8	12.5	21	-	603	-	72
37X12.50R20LT 127Q ***	E	003805	BW	8.5-11.0	11.0	36.8	13.6	21	-	570	-	84

22" Rim Diameter - FLOTATION												
35X12.50R22LT 117Q **	E	003814	BW	8.5-11.0	10.0	34.8	12.5	21	-	603	-	74
37X13.50R22LT 123Q ***	E	003806	BW	8.5-11.0	11.0	36.8	13.6	21	-	570	-	82

\* Conditions apply. See FirestoneTire.com/warranty for details.

Rev: 1/2024 EN

Firestone Americas Tire Operations, LLC.



# TRANSFORCE™ HT 2

COMMERCIAL HIGHWAY



## BECAUSE EVERY JOB IS WORTH DOING RIGHT

### Features & Benefits




All-season performance



Delivers solid traction in wet conditions to help reduce the risk of hydroplaning<sup>1</sup>



Tread design provides great chip and tear resistance<sup>1</sup>



**Optimized Tire Profile**  
to help improve uneven wear, even with heavy loads<sup>1</sup>

**Sawtooth Edge Siping**  
provide biting edges in snow while maintaining block stiffness

**Full Depth Lateral Slots**  
provide water evacuation to help reduce the risk of hydroplaning<sup>1</sup>

# Firestone

<sup>1</sup>As compared to the Firestone Transforce HT.



# TRANSFORCE™ HT 2

## Top Fitments

- Dodge Ram 3500
- Chevrolet Silverado 2500
- Ford F-250 XL
- Ford E-250

## Warranty\*

- Gold Pledge Limited Warranty
- 90-Day Buy & Try™ Guarantee



## Tire Specifications

Tire Size and Service Description	Lead Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd)	Minimum Dual Spacing	Revs Per Mile	UTQG	Wt.
-----------------------------------	------------	-------------	------------------	---------------------	----------------------	-----------------------	-----------------------	--------------------	----------------------	---------------	------	-----

16" Rim Diameter - LT METRIC												
LT215/65R16 115/112R	E	002758	BW	5.5-7.0	6.0	30.4	8.5	14	9.9	685	-	37
LT235/65R16 120/116R	E	002759	BW	6.0-7.5	6.5	31.7	9.3	15	10.8	656	-	40
LT225/75R16 115/112R	E	002760	BW	6.0-7.0	6.0	29.3	8.8	14	10.2	711	-	35
LT245/75R16 120/116R	E	002761	BW	6.5-8.0	7.0	30.5	9.8	14	11.3	684	-	39
LT265/75R16 123/120R	E	002762	BW	7.0-8.0	7.5	31.7	10.5	15	12.2	658	-	44

17" Rim Diameter - LT METRIC												
LT235/60R17 120/117R	E	002766	BW	6.0-7.5	6.5	31.8	9.3	15	10.8	655	-	43
LT225/75R17 116/113R	E	002774	BW	6.0-7.5	6.0	30.3	8.8	14	10.2	687	-	36
LT245/75R17 121/118R	E	002777	BW	6.5-7.5	7.0	31.5	9.8	14	11.3	661	-	41
LT245/70R17 119/116R	E	002767	BW	6.5-8.0	7.0	30.6	9.8	14	11.3	682	-	41
LT245/70R17 -R	E	015125	BW	-	-	-	-	-	-	-	-	-
LT265/70R17 121/118R	E	013870	BW	7.0-8.5	8.0	31.7	10.7	15	-	658	-	44
LT285/70R17 121/118R	E	004371	BW	7.5-9.0	8.5	32.8	11.5	16	13.4	636	-	50

18" Rim Diameter - LT METRIC												
LT265/70R18 124/121R	E	013869	BW	7.0-9.0	8.0	32.6	10.7	15	-	638	-	47
LT275/70R18 125/122S	E	002778	BW	7.0-8.5	8.0	33.2	11.0	16	12.8	628	-	51
LT275/70R18 125/122S	E	014356	BW	-	-	-	-	-	-	-	-	-
LT275/65R18 123/120S	E	013987	BW	7.5-9.0	8.0	32.1	11.0	16	-	649	-	47

20" Rim Diameter - LT METRIC												
LT275/65R20 126/123S	E	004369	BW	7.5-9.5	8.0	34.1	11.0	16	12.8	611	-	53
LT265/60R20 121/118S	E	004372	BW	7.5-9.5	8.0	32.5	10.7	15	12.4	641	-	51
LT285/60R20 125/122R	E	005286	BW	8.0-10.0	8.5	33.5	11.5	16	13.4	623	-	50

## Tire Specifications Legend

△ B-Silent	BW Blackwall	~ Pinned for #12 Stud Sizes
* OEM Tire	OWL Outline White Letter	f Pinned for #15 Stud Sizes
‡ MOE (Mercedes Exclusive)	XL Extra Load (XL)	** Pinned for #16 Stud Sizes
^ RFT (Run Flat Tire)	◆ Pinned for #11 Stud Sizes	*** Pinned for #17 Stud Sizes



# TRANSFORCE™ CV

EURO COMMERCIAL VAN - HIGHWAY



EURO COMMERCIAL VAN

## BUILT TO KEEP YOU ON THE ROAD IN ANY WEATHER

### Features & Benefits




All-season performance



Delivers solid traction in wet conditions while maintaining a quiet ride



Improved fuel efficiency<sup>1</sup>



**Optimized Tire Profile**  
to help improve uneven wear, even with heavy loads<sup>1</sup>

**Sawtooth Edge Siping**  
provides biting edges in snow while maintaining block stiffness

**Full Depth Lateral Slots**  
provide water evacuation to help reduce the risk of hydroplaning<sup>1</sup>

# Firestone

<sup>1</sup>As compared to the Firestone Transforce HT.





# TRANSFORCE™ CV

## Top Fitments

- Ford Transit Connect
- Ford Transit
- Ram Promaster City

## Warranty\*

- Gold Pledge Limited Warranty
- 90-Day Buy & Try™ Guarantee



## Tire Specifications Legend

Δ B-Silent	BW Blackwall	~ Pinned for #12 Stud Sizes
* OEM Tire	OWL Outline White Letter	f Pinned for #15 Stud Sizes
‡ MOE (Mercedes Exclusive)	XL Extra Load (XL)	** Pinned for #16 Stud Sizes
^ RFT (Run Flat Tire)	◆ Pinned for #11 Stud Sizes	*** Pinned for #17 Stud Sizes

## Tire Specifications

Tire Size and Service Description	Lead Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd)	Minimum Dual Spacing	Revs Per Mile	UTQG	Wt.
<b>16" Rim Diameter</b>												
195/75R16C 107/105R	D	004708	BW	5.0-6.0	5.5	27.5	7.7	12	8.9	758	-	27
225/75R16C 121/120R	E	011486	BW	6.0-7.0	6.0	29.3	8.8	12	10.1	711	-	36
235/65R16C 121/119R	E	004709	BW	6.5-8.5	7.0	28.0	9.5	13	10.9	743	-	35
215/65R16 97H	XL	008699	BW	6.0-7.5	7.0	25.3	8.9	12	-	824	500 B B	25
<b>17" Rim Diameter</b>												
215/50R17 95H	XL	008698	BW	6.0-7.5	7.0	25.5	8.9	12	-	817	500 B B	25



# TRANSFORCE™ AT2

COMMERCIAL - ALL TERRAIN



WHEREVER THE JOB IS, DEPEND ON FIRESTONE TO GET YOU THERE

## Features & Benefits




Strong for on-road/off-road



Improved wet performance as compared to original Transforce AT tire<sup>1</sup>



Longer-lasting performance<sup>1</sup>



**Built with a Chip and Tear Resistant Compound**  
tough enough to deal with rough road conditions like gravel

**Deep Tread Features**  
provide confident wet and snow traction

**Pattern Features Combined with an Innovative Tread-To-Road Contact Footprint**  
help retain performance over the course of the tire service life

# Firestone

<sup>1</sup>As compared to Firestone Transforce AT.



# TRANSFORCE™ AT2

## Top Fitments

- Chevrolet Silverado 3500
- Dodge Ram 3500

## Warranty\*

- Gold Pledge Limited Warranty
- 90-Day Buy & Try™ Guarantee



## Tire Specifications

Tire Size and Service Description	Lead Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd)	Minimum Dual Spacing	Revs Per Mile	UTQG	Wt.
-----------------------------------	------------	-------------	------------------	---------------------	----------------------	-----------------------	-----------------------	--------------------	----------------------	---------------	------	-----

16" Rim Diameter - LT METRIC												
L7256/6R16 115/12R	E	000176	BW	5.5-7.0	6.0	30.4	8.5	16	9.9	685	-	37
L7235/6R16 120/16R	E	000179	BW	6.0-7.5	6.5	31.7	9.3	17	10.8	656	-	41
L7225/7R16 115/12R	E	000180	BW	6.0-7.0	6.0	29.3	8.8	16	10.2	711	-	36
L7245/7R16 120/16R	E	000181	BW	6.5-8.0	7.0	30.5	9.8	17	11.3	684	-	41
L7265/7R16 123/120R	E	000182	BW	7.0-8.0	7.5	31.7	10.5	17	12.2	658	-	43

17" Rim Diameter - LT METRIC												
L7235/6R17 120/17R	E	000185	BW	6.0-7.5	6.5	31.8	9.3	17	10.8	655	-	41
L7225/7R17 116/13R	E	000183	BW	6.0-7.5	6.0	30.3	8.8	16	10.2	687	-	38
L7245/7R17 121/18R	E	000184	OWL	6.5-7.5	7.0	31.5	9.8	17	11.3	661	-	43
L7245/7R17 119/16R	E	000186	BW	6.5-8.0	7.0	30.6	9.8	17	11.3	682	-	41
L7265/7R17 121/18R	E	013868	BW	7.0-8.5	8.0	31.7	10.7	17	-	658	-	45
L7265/7R17 121/18R	E	000780	BW	7.5-9.0	8.5	32.8	11.5	18	13.4	636	-	50

18" Rim Diameter - LT METRIC												
L7265/7R18 124/121R	E	000188	BW	7.0-9.0	8.0	32.6	10.7	17	12.4	638	-	50
L7275/7R18 125/122R	E	013989	BW	7.0-8.5	8.0	33.2	11.0	18	-	628	-	51
L7275/7R18 125/122R	E	014357	OWL	-	-	-	-	18	-	-	-	51
L7275/6R18 123/120R	E	013988	BW	7.5-9.0	8.0	32.1	11.0	16	-	649	-	48

20" Rim Diameter - LT METRIC												
L7275/6R20 126/123R	E	000191	BW	7.5-9.5	8.0	34.1	11.0	16	12.8	611	-	51
L7265/6R20 121/18R	E	000192	BW	7.5-9.5	8.0	32.5	10.7	15	12.4	641	-	47
L7265/6R20 125/122R	E	014358	OWL	-	-	-	-	-	-	-	-	-

## Tire Specifications Legend

△ B-Silent	BW Blackwall	~ Pinned for #12 Stud Sizes
* OEM Tire	OWL Outline White Letter	f Pinned for #15 Stud Sizes
‡ MOE (Mercedes Exclusive)	XL Extra Load (XL)	** Pinned for #16 Stud Sizes
^ RFT (Run Flat Tire)	◆ Pinned for #11 Stud Sizes	*** Pinned for #17 Stud Sizes



# WINTERFORCE™ 2

STUDDABLE WINTER



## BUILT TO KEEP YOU WORKING THROUGH THE WINTER

### Features & Benefits




Winter performance and grip you can rely on



Long-lasting performance



Great value



**Special Cold Weather Compound, Open Shoulder Slots, and Tread Design** provide better grip in wintry conditions vs. an all-season tire<sup>1</sup>

**Full Depth Tread Features** provide long-lasting performance winter after winter

**Great Winter Performance** certified with the 3-Peak Mountain Snowflake designation and pinned for size #11 studs

# Firestone

<sup>1</sup>As compared to the Firestone FR710 tire.



# WINTERFORCE™ 2

## Top Fitsments

- Chevrolet Malibu
- Honda Odyssey

## Warranty\*

- Winter Tire Limited Warranty



WINTER TIRE  
LIMITED WARRANTY

## Tire Specifications Legend

△ B-Silent	BW Blackwall	~ Pinned for #12 Stud Sizes
* OEM Tire	OWL Outline White Letter	f Pinned for #15 Stud Sizes
‡ MOE (Mercedes Exclusive)	XL Extra Load (XL)	** Pinned for #16 Stud Sizes
^ RFT (Run Flat Tire)	◆ Pinned for #11 Stud Sizes	*** Pinned for #17 Stud Sizes

## Tire Specifications

Tire Size and Service Description	Load Range	Item Number	St sidewall Styling	Approved Widths	Measuring Widths	Overall Diameter	Overall Width	Tread Depth (32nd Mile)	UTQG	Wt	
<b>14" Rim Diameter</b>											
195/65R14 86S ◆		148891	BW	5.0-6.5	5.5	23.5	7.4	12	888	-	19
<b>15" Rim Diameter</b>											
P205/75R15 97S ◆		148880	BW	5.0-7.0	5.5	27.1	8.0	12	768	-	22
205/70R15 96S ◆		148863	BW	5.0-7.0	6.0	26.3	8.2	12	791	-	21
215/70R15 95S ◆		149048	BW	5.5-7.0	6.5	26.9	8.7	12	775	-	27
195/65R15 88S ◆		148844	BW	5.0-6.5	5.5	24.5	7.4	12	852	-	20
195/65R15 91S ◆		148895	BW	5.5-7.0	6.0	25.0	7.9	12	833	-	25
185/65R15 84S ◆		148927	BW	5.0-6.5	5.5	23.7	7.4	12	878	-	18
195/65R15 88S ◆		148878	BW	5.5-7.0	6.0	24.2	7.9	12	860	-	23
<b>16" Rim Diameter</b>											
205/65R16 85S ◆		003844	BW	5.5-7.5	6.0	26.5	8.2	12	787	-	21
225/65R16 100S ◆		149235	BW	6.0-8.0	6.5	27.5	9.0	12	758	-	26
205/60R16 92S ◆		149099	BW	5.5-7.5	6.0	26.7	8.2	12	812	-	22
215/60R16 95S ◆		149133	BW	6.0-7.5	6.5	26.1	8.7	13	797	-	24
225/60R16 98S ◆		149164	BW	6.0-8.0	6.5	26.6	9.0	12	783	-	24
205/65R16 91S ◆		149082	BW	5.5-7.5	6.5	24.9	8.4	12	837	-	23
215/65R16 93S ◆		149116	BW	6.0-7.5	7.0	25.3	8.9	12	824	-	20
205/60R16 87S ◆		149095	BW	5.5-7.5	6.5	24.1	8.4	12	865	-	20
<b>17" Rim Diameter</b>											
215/65R17 95S ◆		149252	BW	6.0-7.5	6.5	28.0	8.7	12	743	-	24
215/65R17 94S ◆		149235	BW	6.0-7.5	7.0	26.3	8.9	12	792	-	22
225/65R17 97S ◆		149286	BW	6.0-8.0	7.0	26.8	9.2	12	778	-	23
235/65R17 98S ◆		149320	BW	6.5-8.5	7.5	27.2	9.7	12	767	-	26
205/60R17 93S ◆	XL	006438	BW	5.5-7.5	6.5	25.1	8.4	12	829	-	23
215/60R17 95S ◆	XL	006352	BW	6.0-7.5	7.0	25.5	8.9	12	817	-	23
225/60R17 94S ◆		149269	BW	6.0-8.0	7.0	25.9	9.2	12	804	-	23
225/65R17 91S ◆		006433	BW	7.0-9.5	7.5	25.0	8.9	12	835	-	22
<b>18" Rim Diameter</b>											
225/60R18 100S ◆		149337	BW	6.0-8.0	6.5	28.6	9.0	12	728	-	27
225/65R18 96S ◆		006863	BW	6.0-8.0	7.0	27.8	9.2	12	749	-	24
225/60R18 95S ◆		006439	BW	6.0-8.0	7.0	26.9	9.2	12	775	-	20
235/60R18 101S ◆	XL	008662	BW	6.5-8.5	7.5	27.3	9.7	12	764	-	28
225/65R18 95S ◆	XL	008861	BW	7.0-8.5	7.5	25.9	8.9	12	803	-	25
235/65R18 94S ◆		006434	BW	7.5-9.0	8.0	26.3	9.3	12	791	-	24
225/60R18 92S ◆	XL	008660	BW	7.5-9.0	8.0	25.1	9.1	12	831	-	25



# WINTERFORCE™ 2 UV

STUDDABLE WINTER



## BUILT TO KEEP YOU WORKING THROUGH THE WINTER

### Features & Benefits




Winter performance and grip you can rely on



Long-lasting performance



Great value



**Special Cold Weather Compound, Open Shoulder Slots, and Tread Design** provide grip in wintry conditions

**Full Depth Tread Features** provide long-lasting performance winter after winter

**Great Winter Performance** certified with the 3-Peak Mountain Snowflake designation and pinned for size #11 studs

# Firestone



# WINTERFORCE™ 2 UV

## Top Fitments

- Toyota Tacoma
- Chevrolet Equinox
- Toyota Rav 4
- Chevrolet Silverado 1500

## Warranty\*

- Winter Tire Limited Warranty



WINTER TIRE  
LIMITED WARRANTY

## Tire Specifications

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (3/32")	Revs Per Mile	UTQG	Wt
-----------------------------------	------------	-------------	------------------	---------------------	----------------------	-----------------------	-----------------------	---------------------	---------------	------	----

15" Rim Diameter											
P215/75R15 100S *		146368	BW	5.5-7.0	6.0	27.7	8.5	12	753	-	25
P225/75R15 102S *		148419	BW	6.0-7.5	6.0	28.3	8.8	12	736	-	26
P235/75R15 108S *	XL	148470	BW	6.0-8.0	6.5	28.9	9.3	12	722	-	31
P265/75R15 112S *		148606	BW	7.0-9.0	7.5	30.7	10.5	12	679	-	35

16" Rim Diameter											
P225/75R16 104S *		148436	BW	6.0-7.5	6.0	29.3	8.8	12	711	-	28
P245/75R16 108S *		148572	BW	6.5-8.0	7.0	30.5	9.8	12	694	-	36
P265/75R16 114S *		003454	BW	7.0-9.0	7.5	31.7	10.5	12	658	-	37
P215/70R16 100S *		148232	BW	5.5-7.0	6.5	27.9	8.7	12	747	-	25
P225/70R16 102S *		148286	BW	6.0-7.5	6.5	28.4	9.0	12	733	-	27
P235/70R16 104S *		148453	BW	6.0-8.0	7.0	29.0	9.5	12	719	-	29
P245/70R16 106S *		148521	BW	6.5-8.0	7.0	29.5	9.8	12	705	-	34
P255/70R16 108S *		148589	BW	6.5-8.5	7.5	30.1	10.2	12	693	-	35
265/70R16 112S *		148317	BW	7.0-9.0	8.0	30.6	10.7	12	680	-	37
P215/65R16 98S *		148215	BW	6.0-7.5	6.5	27.0	8.7	12	771	-	25

17" Rim Diameter											
P245/70R17 108S *		148538	BW	6.5-8.0	7.0	30.6	9.8	12	682	-	34
255/70R17 112S *		006012	BW	6.5-8.5	8.0	31.1	10.2	12	670	-	36
265/70R17 115S *		148351	BW	7.0-9.0	8.0	31.7	10.7	12	658	-	39
P225/65R17 102S *		148249	BW	6.0-8.0	6.5	28.5	9.0	12	731	-	27
P235/65R17 104S *		148300	BW	6.5-8.5	7.0	29.1	9.5	12	717	-	30
P245/65R17 106S *		148487	BW	7.0-8.5	7.0	29.5	9.8	12	705	-	32
P255/65R17 110S *		009011	BW	7.0-9.0	8.0	30.1	10.2	12	693	-	33
P215/60R17 96S *		003855	BW	6.0-7.5	6.5	27.2	8.7	12	767	-	24
225/60R17 98S *		006429	BW	6.0-8.0	6.5	27.6	9.0	12	754	-	26
P235/60R17 102S *		003856	BW	6.5-8.5	7.0	28.1	9.5	12	741	-	28

18" Rim Diameter											
P235/65R18 106S *		006007	BW	6.5-8.5	7.0	30.0	9.5	12	693	-	32
P255/65R18 109S *		006009	BW	7.0-9.0	7.5	31.1	10.2	12	671	-	34
P265/65R18 112S *		006008	BW	7.5-9.5	8.0	31.5	10.7	12	660	-	36
P272/65R18 114S *		003854	BW	7.5-9.5	8.0	32.1	11.0	12	649	-	40
265/60R18 110S *		003857	BW	7.5-9.5	8.0	30.5	10.7	12	683	-	35
P235/55R18 100S *		003853	BW	6.5-8.5	7.5	28.2	9.7	12	740	-	27

## Tire Specifications Legend

△ B-Silent	BW Blackwall	~ Pinned for #12 Stud Sizes
* OEM Tire	OWL Outline White Letter	f Pinned for #15 Stud Sizes
‡ MOE (Mercedes Exclusive)	XL Extra Load (XL)	** Pinned for #16 Stud Sizes
^ RFT (Run Flat Tire)	◆ Pinned for #11 Stud Sizes	*** Pinned for #17 Stud Sizes

# WINTERFORCE™ LT

STUDDABLE WINTER



## PATENTED TREAD TO TAME WINTER


### Features & Benefits



Delivers solid traction in snowy, icy and wet conditions



Directional tread design provides a comfortable ride



**High Sipe Density Biting Edges**  
provide additional traction in snowy, wet and icy conditions

**Pinned For Studs**  
to help promote solid ice traction when installed with optional studs (size #15)

**Directional Tread Pattern**  
helps provide traction with a quiet, comfortable ride

# Firestone





# WINTERFORCE™ LT

## Top Fitments

- Chevrolet Silverado
- Dodge Ram 3500
- Ford F-150

## Warranty\*

- Winter Tire Limited Warranty



WINTER TIRE  
LIMITED WARRANTY

## Tire Specifications Legend

△ B-Silent	BW Blackwall	~ Pinned for #12 Stud Sizes
* OEM Tire	OWL Outline White Letter	f Pinned for #15 Stud Sizes
‡ MOE (Mercedes Exclusive)	XL Extra Load (XL)	** Pinned for #16 Stud Sizes
^ RFT (Run Flat Tire)	◆ Pinned for #11 Stud Sizes	*** Pinned for #17 Stud Sizes

## Tire Specifications

Tire Size and Service Description	Lead Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd)	Minimum Spacing	Revs Per Mile	UTQG	Wt.
-----------------------------------	------------	-------------	------------------	---------------------	----------------------	-----------------------	-----------------------	--------------------	-----------------	---------------	------	-----

16" Rim Diameter - LT METRIC												
LT215/65R16 115/112R f	E	246488	BW	5.5-7.0	6.0	30.4	8.5	16	9.9	681	-	37
LT225/75R16 115/112R f	E	246250	BW	6.0-7.0	6.0	29.3	8.8	16	10.2	706	-	37
LT245/75R16 120/116R f	E	246267	BW	6.5-8.0	7.0	30.5	9.8	17	11.3	679	-	43
LT265/75R16 123/120R f	E	246284	BW	7.0-8.0	7.5	31.7	10.5	17	12.2	653	-	46
LT285/75R16 126/123R f	E	246386	BW	7.5-9.0	8.0	32.8	11.3	19	13.1	629	-	54

17" Rim Diameter - LT METRIC												
LT235/60R17 120/117S f	E	246369	BW	6.0-7.5	6.5	31.8	9.3	17	10.8	651	-	43
LT225/75R17 116/113R f	E	246420	BW	6.0-7.5	6.0	30.3	8.8	16	10.2	681	-	40
LT245/75R17 121/118R f	E	246335	BW	6.5-7.5	7.0	31.5	9.8	17	11.3	657	-	44
LT255/75R17 111/109S f	C	232973	BW	6.5-8.5	7.0	32.1	10.0	17	11.7	646	-	42
LT245/70R17 119/116R f	E	246454	BW	6.5-8.0	7.0	30.6	9.8	17	11.3	679	-	46
LT265/70R17 121/118R f	E	246471	BW	7.0-8.5	8.0	31.7	10.7	18	12.4	653	-	50

18" Rim Diameter - LT METRIC												
LT265/70R18 124/121R f	E	066005	BW	7.0-9.0	8.0	32.6	10.7	18	12.4	638	-	50
LT275/70R18 125/122R f	E	246403	BW	7.0-8.5	8.0	33.2	11.0	19	12.8	624	-	54
LT275/65R18 123/120R f	E	246437	BW	7.5-9.0	8.0	32.1	11.0	19	12.8	645	-	52

20" Rim Diameter - LT METRIC												
LT275/65R20 126/123R f	E	232871	BW	7.5-9.5	8.0	34.1	11.0	18	12.8	611	-	57



# WINTERFORCE™ CV

DEDICATED WINTER EURO COMMERCIAL VAN



EURO COMMERCIAL VAN

## HEAVY-DUTY WINTER PERFORMANCE YOU CAN COUNT ON

### Features & Benefits




Winter performance



Delivers solid traction in wet conditions while maintaining a quiet ride



Long-lasting performance



**5-Rib Tread Design with Full Depth Grooves**  
help evacuation in deep water and slush

**Zig-Zag Sawtooth Sipes**  
provide biting edges in snow while maintaining block stiffness

**High Sipe Density Biting Edges**  
provide additional traction in snow, wet and ice conditions

# Firestone

# WINTERFORCE™ CV



## Top Fitments

- Ford Transit Connect
- Ford Transit
- Ram Promaster City

## Warranty\*

- Winter Tire Limited Warranty



WINTER TIRE  
LIMITED WARRANTY

## Tire Specifications Legend

Δ	B-Silent	BW	Blackwall	~	Pinned for #12 Stud Sizes
*	OEM Tire	OWL	Outline White Letter	f	Pinned for #15 Stud Sizes
‡	MOE (Mercedes Exclusive)	XL	Extra Load (XL)	**	Pinned for #16 Stud Sizes
^	RFT (Run Flat Tire)	◆	Pinned for #11 Stud Sizes	***	Pinned for #17 Stud Sizes

## Tire Specifications

Tire Size and Service Description	Lead Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd)	Minimum Dual Spacing	Revs Per Mile	UTQG	Wt.
<b>16" Rim Diameter</b>												
195/75R16C 107/105R	D	005843	BW	5.0-6.0	5.5	27.5	7.7	12	8.9	758	-	30
225/75R16C 121/120R	E	011490	BW	6.0-7.0	6.0	29.3	8.8	12	10.1	711	-	36
235/65R16C 121/119R	E	005842	BW	6.5-8.5	7.0	28.0	9.5	13	10.9	743	-	43
215/65R16 97R	XL	008897	BW	6.0-7.5	7.0	25.3	8.9	12	-	824	-	25
<b>17" Rim Diameter</b>												
215/50R17 95R	XL	008696	BW	6.0-7.5	7.0	25.5	8.9	12	-	817	-	25

**81%**  
COVERAGE

An 11% coverage advantage  
vs. the Firestone  
Champion Fuel Fighter<sup>1</sup>

## STOCK THE TOURING TIRE THAT SHATTERS EXPECTATIONS

With its broad coverage, 65,000 limited mileage warranty<sup>2</sup> and impressive weather versatility, Firestone WeatherGrip tire creates opportunities to upgrade a wide range of customers. Now you can take them from a touring tire without weather capabilities to one with the unmatched weather traction of Firestone WeatherGrip tires.



### 1. 3-PEAK MOUNTAIN SNOWFLAKE CERTIFIED<sup>3</sup>

Built to perform better in snow and ice—even against other "All-Weather" competitors.

### 2. HYDRO-GRIP™ TECHNOLOGY<sup>4</sup>

Open shoulder slots cut through water to help reduce the risk of hydroplaning.

### 3. TRACTIONTECH™ PACKAGE<sup>7</sup>

Full-depth tread + interlocking sipes help ensure wet and snow performance over the life of the tire.

<sup>1</sup>Conditions apply. See [FirestoneTire.com/warranty](http://FirestoneTire.com/warranty) for details.  
<sup>2</sup>Based on U.S. registered vehicle information data for Sedans, Minivans and CUVs (July 2020).  
<sup>3</sup>With the Firestone WeatherGrip tire's three-peak mountain snowflake certification.  
<sup>4</sup>Hydro-Grip™ Package features full-depth grooves to help provide enhanced water evacuation, open shoulder slots help provide enhanced water evacuation, and a rounded footprint that pierces water to help improve hydroplaning resistance.  
<sup>7</sup>TractionTech™ Package features a full-depth tread design that is engineered to maintain performance throughout the tire's limited mileage warranty. Also, interlocking sipes that create more edges for enhanced snow and wet performance longer through the tire's limited mileage warranty.